

## Rubber Air & Water Discharge Hose (A200)

<b>Application:</b>	Water transfer hose - also suitable for air transfer
<b>Tube:</b>	Black, smooth, SBR rubber
<b>Reinforcement:</b>	High strength synthetic cord
<b>Cover:</b>	Black, smooth (wrapped finish), EPDM rubber compound, abrasion, weather and ozone resistant
<b>Temperature:</b>	-35°C to 70°C
<b>Special Features:</b>	<ul style="list-style-type: none"> <li>• Ozone resistance</li> <li>• Minimum cut length of 5 mtrs, charges apply for cutting hose.</li> </ul>



Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
A200012	13	20	145	1	435	165	0.22	20	13.27
A200020	19	27	145	1	435	190	0.29	20, 60	13.67
A200025	25	33	145	1	435	254	0.46	20, 60	15.38
A200032	32	41	145	1	435	320	0.76	20, 60	20.02
A200040	38	48	145	1	435	380	1.05	20, 60	25.39
A200050	51	60	145	1	435	508	1.49	20, 60	33.92
A200065	63.5	75	145	1	435	635	2.07	20, 60	49.47
A200080	76	88	145	1	435	762	2.66	20, 60	65.45
A200090	90	102	145	1	435	900	3.37	20, 60	81.24
A200100	102	114	145	1	435	1016	4.07	20, 60	88.00
A200125	127	140	145	1	435	1270	5.40	20	141.04
A200150	152	164	145	1	435	1524	6.44	20	168.16
A200200	203	217	145	1	435	2030	7.74	20	200.70
A200254	254	270	145	1	435	3048 <sup>1</sup>	10.1	20	495.33
A200300	305	320	145	1	435	3660 <sup>1</sup>	11.9	20	676.97

Price Group: HR  
DB20

## Rubber Petrol & Oil Aviation Refuelling Hose AS2683 (A455)

<b>Application:</b>	Mandrel built rubber hose, designed for aircraft re-fuelling operations
<b>Tube:</b>	Black, smooth, high quality nitrile rubber compound, resistant up to 50% maximum aromatic content
<b>Reinforcement:</b>	High strength synthetic cord
<b>Cover:</b>	Black, smooth (wrapped finish), high grade chloroprene, anti-static weather, ozone, abrasion and oil resistant
<b>Temperature:</b>	-25°C to 70°C
<b>Features:</b>	• Minimum cut length of 10 mtrs, charges apply for cutting hose.
<b>Standards:</b>	According to: BS 3158 - API 1529; EN 1361 - AS 2683; 2010 VG 95955 - NFPA 407. Grade 2, kind 3



Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
A455025	25	38.5	300	2.1	1200	150 <sup>1</sup>	0.784	60	120.19
A455032	32	45.5	300	2.1	1200	180	0.966	60	130.81
A455040	38	52	300	2.1	1200	200	1.42	60	158.07
A455050	50	68	300	2.1	1200	250	1.76	60	196.23
A455065	63.5	79.5	300	2.1	1200	300	2.28	60	305.25
A455080	75	92.5	300	2.1	1200	450	2.63	60	381.56
A455100	100	118	300	2.1	1200	750	3.67	60	545.08

Price Group: HR  
DB13

<sup>1</sup> Denotes figure is calculated as theoretical.

Complete hose data specification sheets are available upon request.



1300 134 651  
dixonvalve.com.au

All prices exclude GST.  
ADPL718