


## PVC Clear Vinyl Tube (CVT)

<b>Application:</b>	Low pressure air, water, food, beverage and medical drainage
<b>Tube:</b>	Clear smooth tubing, blue tint
<b>Temperature Range:</b>	-10°C to 60°C
<b>Special Features:</b>	Non-toxic; food grade
<b>Standards:</b>	Complies with AS2070:1999 for food contact



Part No.	Dimensions (mm)		Working Pressure		BP PSI	Weight kg/mtr	Length (mtr)	Price \$ per mtr / coil
	ID	OD	PSI	MPa				
H1600330C	3	5	114	0.8	342	0.02	30	17.08
H16003200R	3	5	114	0.8	342	0.02	200	108.49
H1600530C	5	8	102	0.7	305	0.03	30	31.74
H16005100S	5	8	102	0.7	305	0.03	100	98.73
H1600630C	6	9	89	0.6	267	0.04	30	35.40
H16006100S	6	9	89	0.6	267	0.04	100	117.99
H1600830C	8	11	73	0.5	219	0.05	30	39.87
H16008100S	8	11	73	0.5	219	0.05	100	142.39
H1601030C	10	13	60	0.4	180	0.07	30	48.98
H1601075R	10	13	60	0.4	180	0.07	75	122.46
H1601230C	12.5	16.5	60	0.4	180	0.12	30	75.20
H1601250S	12.5	16.5	60	0.4	180	0.12	50	124.98
H1601630C	16	20	60	0.4	180	0.14	30	102.52
H1602030C	20	24	50	0.3	150	0.16	30	119.61
H1602530C	25	31	44	0.3	132	0.32	30	214.16
H1603230C	32	38	29	0.2	87	0.4	30	301.88
H1604015C	40	46	29	0.2	87	0.56	15	233.53
H1605015C	50	60	29	0.2	87	1	15	330.35

Price Group: HP

DA20

C = Coil, R = Reel, S = Spool

## PVC Drum Pump

<b>Application:</b>	Petrol and oil dispensing hose featuring high flexibility at low temperatures. Dispensing from overhead tanks and drums. UV stabilised
<b>Tube:</b>	Black PVC
<b>Reinforcing:</b>	Polyester
<b>Cover:</b>	Black ribbed PVC
<b>Temperature Range:</b>	-5°C to 60°C
<b>Special Feature:</b>	UV stabilised



Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Length mtr	Price \$ per mtr / coil
	ID	OD	PSI	MPa					
H1102520	25	34	150	0.96	600	155	0.35	20	249.39
H1103220	32	42	150	0.96	600	320	0.90	20	348.38

Price Group: HP

DA09

Complete hose data specification sheets are available upon request.



1300 134 651  
dixonvalve.com.au

All prices exclude GST.  
ADPL718