



ANCHOR MARK LINE MARKING PAINT

PRODUCT DESCRIPTION:

Anchor Mark Line Marking is a quick dry, high opacity marking paint used for line marking in a variety of applications including car parks, warehouses, factories and sporting fields and courts. It creates long lasting lines with a high UV resistance and is available in White, Yellow and Blue

APPLICATIONS: Suitable for use most surfaces including:

- Grass
- Concrete
- Bitumen
- Timber

SURFACE PREPERATION: All surfaces: Remove any loose contaminants by sweeping the surface. All surfaces to be marked should be clean, dry, and free from; oil, grease, dust, dirt, algae, moss, road salts and other contaminants before application is started. Allow surface to dry thoroughly prior to application. Cover any surrounding areas to protect them from spray mist.

DIRECTIONS: Shake the can for a minimum of 1 to 2 minutes after the agitator balls are heard rattling and again frequently during use. **IMPORTANT** - After use do not allow paint to dry in the nozzle - clear nozzle by turning the can so it points upwards and pressing the nozzle for a few seconds to clear the nozzle. Wipe nozzle clean after use.

Best when used with an applicator, speed of movement dictates the density of the line produced.

Do not apply if ambient temperatures fall below 3°C or relative humidity exceeds 90%

DRYING TIMES: @ 25°C < 50%RH

TOUCH DRY - 10 -20 MINS

Drying time may be slower in colder and humid conditions.

COVERAGE: 60-100m x 50mm wide line depending on application

PACK SIZE: 500G

STORAGE: Store away from sources of ignition, naked flames and direct path of sun and preferably in temperatures range 15°C to 30°C.

WARNING: Intentional misuse by deliberately inhaling contents can be harmful or fatal. Do not puncture this container even when empty. Avoid breathing of vapour and mist. Provide adequate ventilation when spraying in confined spaces. Avoid contact with eyes and skin.

HEALTH AND SAFETY: Highly flammable, do not use near fire or open flame. Store in a cool place and out of direct path of the sun. Keep Out Of Reach Of Children. If swallowed seek medical advice immediately or contact the Poisons Information Center on 13 11 26. Spills and leaks can be contained with absorbent material such as sand, earth or saw dust.

FIRST AID: Refer to the Safety Data sheet available at www.cwbrands.com.au/

PROPELLANT: Hydrocarbon





ANCHOR LINE MARKING PAINT

DISCLAIMER:

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure suitability of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.



LINE MARKING

SURVEY MARKING PAINT

Anchor Line Marking Paint is a high-quality paint for marking lines on various surfaces.

- ✓ Designed for easy and precise marking of various surfaces during survey work
- ✓ Provides clear and visible markings for improved accuracy and efficiency
- ✓ Suitable for use in construction, civil engineering, and other surveying tasks

COLOUR LIST

- **LM01**
White
Barcode : 9340885004641
- **LM02**
Yellow
Barcode : 9340885004658
- **LM03**
Blue
Barcode : 9340885004665