

Ref.: 415012



DIGITAL METERED CONTROL VALVE, PG500-14/FM SERIES, 2,5 KG/MIN, GREASE, FLEXIBLE OUTLET, Z-SWIVEL

High pressure grease meter guns with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminium with steel insert for high pressure. Flexible outlet with 3 jaw connector and Z-swivel. High pressure oval gear grease meter with digital display, 1/8" inlet / outlet connection. Works with up to NLGI-2 grease. Shock proof, Clear to read, Increased durability, Easy to replace batteries and calibration function. Aluminium body, Acetal oval gear technology and Strengthened PC cover. Works with two 1,5 V AAA alkaline batteries. Youtube video: <https://youtu.be/wBkymrU0Wv8> Instruction books: 841801 and 841810.

Technical data

Documentation

More information

Compatible fluids	Grease
Maximum free flow delivery	2,5 kg/min (5,5 lb/min)
Accuracy	0.02
Maximum outlet pressure	500 bar (7250 psi)
Operating temperature range	-10 - 55 °C (14-131 °F)
Inlet size	1/4"
Fluid inlet	1/4" BSP (F)
Outlet type	Z-swivel, flexible tube, grease connector
Meter	Digital
Metric	Litres, Gallons, Pints, Quarts
Wetted materials	Aluminium Acetal Nbr Stainless Steel Zinc Plated Steel
Weight	1,5 kg (3 lb)

Technical data

Documentation

More information

[Login](#) or [register](#) to consult this content