

- ▶ MIG SINGLE / DUAL PULSE
- ▶ MIG SYNERGIC / MANUAL
- ▶ MIG GAS / GASLESS
- ▶ DC TIF (LIFT ARC)
- ▶ STICK (MMA)

DUTY CYCLE
30% @ 200A

GENERATOR
10 kVA

PLATE THICKNESS
MAX 8mm

MATERIALS
 - Mild Steel
 - Stainless Steel
 - Carbon Stainless
 - Aluminium (MIG only)



BUDDY



FEATURES

- 200A Output, 15A plug
- Digital LCD Display
- MIG / Stick / TIG Welder
- Dual Pulse MIG
- Suits D100 (1 kg) & D200 (5 kg) Spools
- Runs 0.8 – 1.2mm Wires
- Up to 5.0mm Electrodes
- Spool Gun Ready
- 2T / 4T
- IGBT Technology
- Generator Safe
- VRD - Increased Safety
- Australian Standard AS 60974-6

APPLICATION

- General Repairs & Maintenance
- Sheetmetal & Car Repair
- Rural Applications
- DIY & Home Workshops
- Trade Applications

STANDARD PACKAGE INCLUSIONS

BossWeld Buddy Pulse 200 Inverter Welder 240V
 BZ24 MIG Torch 3Mt fitted for Aluminium
 Tong Electrode Holder 300Amp 1.5Mt
 Earth Clamp 200Amp 2Mt
 Argon Twin Gauge Regulator
 Gas Hose
 0.8/1.0 Contact Tip Spare for Aluminium
 Teflon Liner for Aluminium
 Steel Liner
 Drive Roller 1.0/1.2mm U Groove (Fitted)
 Drive Roller 0.8/1.0mm V Groove Spare
 Drive Roller 0.8/0.9mm Knurled Groove Spare

PART NO: 633200

UPGRADE OPTIONS & ACCESSORIES

BossWeld Universal Large Welders Trolley	600312
Spool Gun Suits Pulse 200 4Mt	97.SPX15.4.2
Spool Gun Suits Pulse 200 8Mt	97.SPX15.8.2
BossWeld Arc Lead Set 3Mt	503325
BossWeld Arc Lead Set 4Mt	504425
26F Series Air-Cooled TIG Torch 4Mt	95.26F.4
26F Series Air-Cooled TIG Torch 8Mt	95.26F.8
Argon Regulator Dual Stage Side Entry	400209

Primary Input Power	Duty Cycle @ 40°C	Open Circuit Voltage	Current Range	IMax	Ieff	Protection/Insulation Class	Wire Diameter Range	Electrode Diameter Range	Thermal Overload	Minimum KVA	Dimensions /Weight
Single Phase 240V 50-60 HZ +/-10%	30% @ 200A	66V	MIG 30-200A TIG 10-200A MMA 10-200A	MIG 38 TIG 29 MMA 41	15A	IP21S / S	0.8mm to 1.2mm	2.5mm to 5.0mm	Yes	10	495x210x330mm / 12kg