



TECHNICAL DATA SHEET

CRC 2-26 Electrical



CRC 2-26 Electrical is a plastic-safe lubricant, penetrant, and corrosion inhibitor in a paraffinic oil base that helps prevent electrical malfunction caused by water penetration, humidity, condensation or corrosion and restores electrical properties after water damage.

A thin residual film with light lubricating properties seals out moisture and provides long-lasting protection for electrical equipment even in difficult environmental conditions.

Specially formulated with high cleaning power, CRC 2-26 Electrical can be used as a degreaser and is ideal for removing fingerprint contamination.

Item Code: 2005

Pack Size: 450g Aerosol

Features and Benefits

- **Preventative maintenance programs:** Increases life expectancy of all electromechanical equipment
- **Eliminates moisture:** Protective film seals out moisture
- **Improves electrical properties**
- **Penetrant:** Frees rusted or corroded parts
- **High dielectric breakdown:** Ideal for high voltage applications
- **Contains no silicone**

Applications

- Electrical connectors
- Motor generator
- Navigation and Telco equipment
- Auto electrical

Typical Properties and Characteristics

Flash Point	100°C
Odour	Methyl salicylate
Appearance	Amber Liquid
Solubility	Insoluble in water
Type of film	Continuous, self-repairing
Coverage	100-140 m ² /1 Litre
Viscosity	4cP @ 20 °C
Lubrication (Falex Test)	Up to 1750 lbs

Flammability	Flammable
Boiling Point	>200°C
% Volatile	75%
Dielectric breakdown	42,000 volts
Specific Gravity	0.88
Propellant	Carbon Dioxide
Film Thickness	1-2 microns
Heat Resistance	Film degradation begins at 150°C



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au



TECHNICAL DATA SHEET

CRC 2-26 Electrical

Certifications and Approvals

1. **NSF Approval: Registration No 134907, Category Code: H2**

[Click here](#) to download the document

Directions

1. For electrical equipment that has been submerged in water, spray liberally on every surface. Allow 2 to 24 hours for the water to be displaced.
2. To protect metals, spray a light even film.
3. To loosen 'frozen' parts, spray liberally and allow to run off.
4. For hard-to-reach areas, use an extension tube.
5. Repeat application, if necessary.

Note: When cleaning surfaces, test a small area first for colour fastness.

Special Precautions

General:

Flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container in accordance with relevant regulations.

Pressurized container: may burst if heated. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 05/2026



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au