



## TECHNICAL DATA SHEET

### CRC Brakleen Force



CRC Brakleen Force, along with Powerjet™ Technology, is formulated to quickly and safely remove brake fluid, grease, oil and other contaminants from brake linings, pads and drums.

CRC Brakleen Force is non chlorinated and does not contain any aromatic hydrocarbons, carbon tetrachloride, silicones or methyl chloroform.

CRC Brakleen Force is non-staining, non-corrosive, and leaves no residue. It cleans without disassembling the brake unit.

**Item Code: 5085**

**Pack Size: 400g Aerosol**

## Features and Benefits

- **Powerjet™ Technology:** Powerful brake & parts cleaner/degreaser
- **Fast evaporation:** Minimises downtime associated with “clean-in-place” cleaning methods
- **Leaves no residue:** Prevents harmful build up and eliminates rinsing and wiping
- **No disassembly required:** Saves time and reduces maintenance cost
- **Low surface tension:** Gives excellent penetration
- **Non-staining and non-corrosive to metals**

## Applications

- Recommended for brake linings, brake pads, drums, cylinders, discs, callipers, clutch plates and equipment tools
- Ideal for cleaning thick build ups and hardened deposits in heavy mechanical equipment

## Typical Properties and Characteristics

|             |                           |
|-------------|---------------------------|
| Flash Point | <10°C                     |
| Odour       | Ethereal                  |
| Appearance  | Clear colourless liquid   |
| Solubility  | Slightly soluble in water |
| Propellant  | Carbon Dioxide            |

|                  |                     |
|------------------|---------------------|
| Flammability     | Extremely flammable |
| Boiling Point    | 55 -120°C           |
| % Volatile       | 100%                |
| Vapour Density   | >Air                |
| Specific Gravity | 0.72                |



TOGETHER, WE GET IT DONE.™

[www.crcindustries.com.au](http://www.crcindustries.com.au)



## TECHNICAL DATA SHEET

### CRC Brakleen Force

## Directions

1. Equipment must be de-energised before cleaning.
2. Spray liberally and allow to run off.
3. Air dry or dry with soft cloth.
4. Repeat the application if necessary.
5. Protect rubber brake parts and painted surfaces from overspray.

**Note:** Test on small area before using.

## Special Precautions

### General:

Extremely Flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Use with adequate ventilation. Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container in accordance with relevant regulations.

Pressurized container: may burst if heated. Do not pierce or burn, even after use. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked-up. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

## Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

## Contact Information

**CRC Industries (Aust) Pty Ltd**  
9 Gladstone Road, Castle Hill  
NSW 2154, Australia

**[www.crcindustries.com.au](http://www.crcindustries.com.au)**  
PH: 1800 224 227  
Email: [info.au@crcind.com](mailto:info.au@crcind.com)

**Disclaimer:** All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

*Technical Data Sheet Version 05/2026*



TOGETHER, WE GET IT DONE.™

**[www.crcindustries.com.au](http://www.crcindustries.com.au)**