



TECHNICAL DATA SHEET

CRC CO Contact Cleaner



CRC CO Contact Cleaner is a plastic safe evaporating cleaner and degreaser for use on sensitive electronic and electrical equipment.

CRC CO Contact Cleaner is formulated to quickly penetrate into hard-to-reach areas and effectively flush away carbon deposits, dirt, light oils, dust, lint and other light contaminants.

CRC CO Contact Cleaner is non-conductive, non-corrosive, and non-staining. It contains **COZOL** - a special proprietary blend of solvents which enhances the cleaning power without damaging plastics.

Item Code: 2015

Pack Size: 150g Aerosol

Features and Benefits

- **Rapid and complete evaporation**
- **Leaves no residue**
- **Plastic safe**
- **High purity formula**
- **Quickly penetrates into hard-to-reach areas**
- **Contains no lubricants, silicones, oils**

Applications

- **Electronic and electrical components:** Connectors, contacts, terminals, motors, plugs, jacks, printed circuit boards, potentiometers, sensors, relays, switches, circuit breakers
- **IT equipment:** Computers, printers, fax machines, memory cards, server room equipment
- **Home appliances repair and maintenance:** Washing machines, dryers, dish washers, vacuum cleaners
- **Hospital and health care equipment:** Diagnostic imaging equipment, hearing aids, laboratory equipment

Typical Properties and Characteristics

Flash Point	<0°C
Odour	Mild ethereal
Appearance	Colourless
Solubility	Insoluble in water
ASTM D-1133 (Kauri-Butanol Value)	31
ASTM D-877 (Dielectric Strength)	40,000 Volt

Flammability	Extremely flammable
Boiling Point	51°C
% Volatile	100%
Vapour Density	4.5
Specific Gravity	0.69
Propellant	Carbon Dioxide
Surface Tension	21 dynes/cm



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au



TECHNICAL DATA SHEET

CRC CO Contact Cleaner

Certifications and Approvals

1. **NSF Approval: Registration No 134911, Category Code: K2**

[Click here](#) to download the document

Directions

1. De-activate and isolate equipment before use.
2. Apply by spraying onto surface. Use extension tube for hard-to-reach areas.
3. Remove cleaning residue with CRC CO Contact Cleaner.
4. Ensure proper ventilation before re-activating equipment.
5. Ventilate after use to dissipate flammable vapours for 30 minutes. Failure to adequately ventilate after use can cause vapours to ignite or explode.

Note: Test on small area before using.

Special Precautions

General:

Extremely Flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Use with adequate ventilation. Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container in accordance with relevant regulations. Pressurized container: may burst if heated. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 05/2026



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au