Gravity Drop Adaptors

Application

- The gravity drop adaptor features an industry-standard API female connection designed to couple directly to the standard API valve leaving either an 80mm (3") or 100mm (4") male Camlock adaptor to be connected to the petroleum unloading hose.

Features

- 80mm (3") or 100mm (4") connections
- Optional sight glass available
- Standard one-piece body
- Various seal options are available

Materials

- Cast aluminium body
- Bronze Camlock arms
- Stainless steel pin and finger rings



4540 without sight glass



4540SGV with sight glass



4540ST

Size		Part Numbers	Description	Seal	Fuel Compatibility
mm	inch				
80	3	4530	4" API to 3" 22.5° drop adaptor, without sight glass	Baylast™ O-ring	Gasoline & Diesel, up to E100 & B100 Biodiesel
100	4	4540	4" API to 4" 22.5° drop adaptor, without sight glass		
		4540ST	4" API to 4" straight drop adaptor, without sight glass		
		4540F	4" API to 4" 22.5° drop adaptor, without sight glass	Nitrile Buna	
80	3	4530SGV	4" API to 3" 22.5° drop adaptor, with sight glass	FKM Flat Seal	Gasoline & Diesel up to B100 Biodiesel
100	4	4540SGV	4" API to 4" 22.5° drop adaptor, with sight glass		
		4540V	4" API to 4" drop adaptor, without sight glass	FKM O-ring	
80	3	4530G	4" API to 3" drop adaptor, without sight glass	Nitrile Buna Flat Gasket	Gasoline & Diesel, up to E100 & B100 Biodiesel
100	4	4540G	4" API to 4" drop adaptor, without sight glass		

Product Group: AS02

Replacement Parts

Part Numbers	Description	To Suit
4500RK	O-ring, arms, pins & Baylast™ O-ring	4530 & 4540
4500RK-V	Arms, pins & FKM O-ring seal	4540V
5205-RK4	Chain & S hook	All
4540SG-RK1	Sight glass repair kit	4530SGV & 4540SGV
4540SG-RK2	Flat Baylast™ gasket	4530SG & 4540SG
4540SG-RK3	Arms, pins & ring	4530SGV & 4540SGV
4500-5	Baylast™ O-ring	4530 & 4540
112054	Nitrile Buna flat gasket	4530G & 4540G

Product Group: AS02



4540SG-RK1



4540SG-RK3