


### Clamp Adaptor x Female NPT

| Clamp Size |      | NPT Thread Size |      | Part Numbers    | Dimension (A) |
|------------|------|-----------------|------|-----------------|---------------|
| mm         | inch | mm              | inch | PL Finish - SF1 | mm            |
| 12.7       | ½    | 6               | ¼    | T22MP-050025PL  | 50.800        |
|            |      | 10              | ⅜    | T22MP-050375PL  | 50.800        |
|            |      | 12              | ½    | T22MP-050PL     | 41.275        |
|            |      | 20              | ¾    | T22MP-050075PL  | 50.800        |
| 19.05      | ¾    | 6               | ¼    | T22MP-075025PL  | 50.800        |
|            |      | 12              | ½    | T22MP-075050PL  | 50.800        |
|            |      | 20              | ¾    | T22MP-075PL     | 57.150        |
| 25.4       | 1    | 25              | 1    | T22MP-100PL     | 57.150        |
| 38.1       | 1½   | 38              | 1½   | T22MP-150PL     | 57.150        |
| 50.8       | 2    | 50              | 2    | T22MP-200PL     | 67.005        |
| 63.5       | 2½   | 65              | 2½   | T22MP-250PL     | 73.025        |
| 76.2       | 3    | 80              | 3    | T22MP-300PL     | 77.975        |
| 101.6      | 4    | 100             | 4    | T22MP-400PL     | 80.137        |


Product Group: AV14



### Weld Caps

| Tube OD Size |      | Part Numbers    |                 | Dimension (A) |
|--------------|------|-----------------|-----------------|---------------|
| mm           | inch | PL Finish - SF1 | PM Finish - SF4 | mm            |
| 12.7         | ½    | T16W-050PL      | T16W-050PM      | 38.10         |
| 19.05        | ¾    | T16W-075PL      | T16W-075PM      | 38.10         |
| 25.4         | 1    | T16W-100PL      | T16W-100PM      | 38.10         |
| 38.1         | 1½   | T16W-150PL      | T16W-150PM      | 38.10         |
| 50.8         | 2    | T16W-200PL      | T16W-200PM      | 38.10         |
| 63.5         | 2½   | T16W-250PL      | T16W-250PM      | 38.10         |
| 76.2         | 3    | T16W-300PL      | T16W-300PM      | 38.10         |
| 101.6        | 4    | T16W-400PL      | T16W-400PM      | 50.80         |
| 152.4        | 6    | T16W-600PL      | T16W-600PM      | 63.50         |

Product Group: AV14




DT-4.1.5-1 (#DT-22)  
ASME BPE 2019

### Solid End Caps

| Tube OD Size |        | Part Numbers    |                 | Dimensions |         |
|--------------|--------|-----------------|-----------------|------------|---------|
| mm           | inch   | PL Finish - SF1 | PM Finish - SF4 | A (mm)     | B (mm)  |
| 12.7         | ½ x ¾  | T16AMP-050075PL | T16AMP-050075PM | 4.826      | 25.400  |
| 38.1         | 1 x 1½ | T16AMP-100150PL | T16AMP-100150PM | 6.350      | 50.546  |
| 50.8         | 2      | T16AMP-200PL    | T16AMP-200PM    | 6.350      | 64.008  |
| 63.5         | 2½     | T16AMP-250PL    | T16AMP-250PM    | 6.350      | 77.470  |
| 76.2         | 3      | T16AMP-300PL    | T16AMP-300PM    | 6.350      | 90.932  |
| 101.6        | 4      | T16AMP-400PL    | T16AMP-400PM    | 7.874      | 119.126 |
| 152.4        | 6      | T16AMP-600PL    | T16AMP-600PM    | 11.178     | 166.624 |

Product Group: AV14



DT-4.1.5-2 (#DT-31)  
ASME BPE 2012