

T-Handle - Female x Female BSP

Size		Part Numbers	Working Pressure		Weight (kg)
mm	inch		PSI	Bar	
6	¼	BBVAGAT006	710	49	0.16
10	⅜	BBVAGAT010	710	49	0.16
15	½	BBVAGAT012	710	49	0.20
20	¾	BBVAGAT020	570	39	0.30
25	1	BBVAGAT025	570	39	0.43

Product Group: AR01



Lever Handle - Male x Female BSP

Operating Temperature

- 20°C - 60°C (class T2 under EN331)

Size		Part Numbers	Working Pressure		Weight (kg)
mm	inch		PSI	Bar	
15	½	BBVAGAMF012	710	49	0.20
20	¾	BBVAGAMF020	570	39	0.30
25	1	BBVAGAMF025	570	39	0.63
40	1 ½	BRBLMF040	363	25	-

Product Group: AR01



Mini Ball Valves

Application

- Domestic water services, heating and air-conditioning plants, and compressed air systems.

Design

- Full bore
- Blow-out proof stem design with chrome ball

Material

- Body: nickel-plated brass
- Seat: PTFE seat
- Ball: chrome-plated brass

End Connection

- Screwed female and male/female BSP
- ISO228 (equivalent to DIN259 and BS2779)


Operating Temperature

- 0°C - 90°C

Female x Female BSP

Size		Part Numbers	Working Pressure	
mm	inch		PSI	Bar
6	¼	MBVFF006	220	15
10	⅜	MBVFF010	220	15
15	½	MBVFF012	220	15
20	¾	MBVFF020	220	15

Product Group: AR01



Male x Female BSP

Size		Part Numbers	Working Pressure	
mm	inch		PSI	Bar
6	¼	MBVMF006	220	15
10	⅜	MBVMF010	220	15
15	½	MBVMF012	220	15
20	¾	MBVMF020	220	15

Product Group: AR01

