

3-Piece In-line Check Valves Stainless Steel

Application

- Used for water, oil, gas, and chemicals.

Features

- Spring loaded in-line check

Material

- Body: 316 stainless steel
- Seat: PTFE
- Disc and spring: 316 stainless steel



End Connection

- Screwed female BSP

Working Pressure

- 1000 PSI CWP (69 bar)

Available Options

- Sizes from 12mm (½") to 100mm (4")
- Female NPT ends up to 50mm (2")

Size		Part Numbers
mm	inch	
12	½	SS3P015-SCV
20	¾	SS3P020-SCV
25	1	SS3P025-SCV
32	1¼	SS3P032-SCV
40	1½	SS3P040-SCV
50	2	SS3P050-SCV

Product Group: VS02

Foot Valves

Application

- General industrial, irrigation and rural services.

Features

- Full bore

Material

- Body: brass
- Spring: stainless steel AISI 302
- Seal: nitrile butadiene rubber
- Strainer Cartridge: SS304



End Connection

- Screwed female BSP conforming to ISO228, DIN259 and BS2779

Temperature

- 0°C to 90°C

Working Pressure

- 90 PSI - 140 PSI

Size		Part Numbers	Working Pressure	
mm	inch		PSI	Bar
20	¾	BFV020	140	10
25	1	BFV025	140	10
32	1¼	BFV032	110	8
40	1½	BFV040	110	8
50	2	BFV050	110	8
65	2½	BFV065	90	6
80	3	BFV080	90	6
100	4	BFV100	90	6

Product Group: VB02