

Fire Hose Reel



Applications

- Used for fire fighting purposes.

Features

- Factory assembled with 19mm ID x 36m hose
- Twist operation brass hose nozzle
- Galvanised and coated mild steel body
- Fixed mounting
- Corrosion resistant waterway
- Watermark certified stop valve

Installation

- Mounting instructions provided with unit
- To be installed in accordance with AS 2441

Specifications

- Minimum discharge rate 0.45 l/s @ 220kpa
- Tested to 1.7MPa as per AS/NZS 1221:1997
- Hose tested in accordance with AS1180.5
- Plate diameter 460mm
- 25mm BSP inlet pipe
- Weight = 23kg
- Box Dimensions = 55 x 50 x 33cm

Standards

- Conforms to AS/NZS 1221: 1997

Standard - Fixed

Part Numbers	Description
FFS-HR-36B	19mm ID x 36m standard fixed

Product Group: FP06

Fire Hose Reel Accessories



Size (mm)	Part Number	Material	Description
19	FFS-HRNB	Brass	Twist nozzle - jet/spray

Product Group: FP08



Size (mm)	Part Number	Material	Description
25	FFS-HRSV	Nickel plated brass	BSPF x BSPF hose reel stop valve

Product Group: FP06



Part Number	Description	Material	Dimensions (mm)
FFS-HRMB	Hose reel mounting bracket	Plated steel	150 W x 100 H

Product Group: FP06



Part Number	Description
FFS-HRGA	Hose reel guide arm

Product Group: FP06