

Dixon™ Premium Type C Coupler x Hose Tail



Size (mm)	Working Pressure (psi)	Part Numbers					
		Aluminium	Bronze	Stainless Steel	Brass	Polypropylene	Nyglass
15	150	ALDC050C	BR050C	SS050C	-	PPC050A¹	NGC050A
20	250	ALDC075C	BR075C	SS075C	BRSS075C	PPC075A	NGC075A
25	250	ALDC100C	BR100C	SS100C	BRSS100C	PPC100A	NGC100A
32	250	ALDC125C	BR125C	SS125C	BRSS125C	PPC125A	NGC125A
40	250	ALDC150C	BR150C	SS150C	BRSS150C	PPC150A	NGC150A
50	250	ALDC200C	BR200C	SS200C	BRSS200C	PPC200A	NGC200A
65	150	ALDC250C	BR250C	SS250C	BRSS250C	-	-
75	125	ALDC300C	BR300C	SS300C	BRSS300C	PPC300A	NGC300A
100	100	ALDC400C	BR400C	SS400C	BRSS400C	PPC400A	NGC400A
125	75	ALDC500C	BR500C	SS500C	-	-	-
150	75	ALDC600C	BR600C	SS600C	-	-	-

Dixon™ Premium Type D Coupler x Female BSP



Size (mm)	Working Pressure (psi)	Part Numbers					
		Aluminium	Bronze	Stainless Steel	Brass	Polypropylene	Nyglass
15	150	ALDC050D	BR050D	SS050D	-	PPD050A¹	NGD050A
20	250	ALDC075D	BR075D	SS075D	BRSS075D	PPD075A	NGD075A
25	250	ALDC100D	BR100D	SS100D	BRSS100D	PPD100A	NGD100A
32	250	ALDC125D	BR125D	SS125D	BRSS125D	PPD125A	NGD125A
40	250	ALDC150D	BR150D	SS150D	BRSS150D	PPD150A	NGD150A
50	250	ALDC200D	BR200D	SS200D	BRSS200D	PPD200A	NGD200A
65	150	ALDC250D	BR250D	SS250D	BRSS250D	-	-
75	125	ALDC300D	BR300D	SS300D	BRSS300D	PPD300A	NGD300A
100	100	ALDC400D	BR400D	SS400D	BRSS400D	PPD400A	NGD400A
125	75	ALDC500D	BR500D	SS500D	-	-	-
150	75	ALDC600D	BR600D	SS600D	-	-	-



- Under no circumstances should camlock couplings be used in compressed air or steam applications
- Polypropylene and nyglass should not be mixed with aluminium fittings