

Dixon™ Premium Type E Adaptor x Hose Tail



Size (mm)	Working Pressure (psi)	Part Numbers					
		Aluminium	Bronze	Stainless Steel	Brass	Polypropylene	Nyglass
15	150	ALDC050E	BR050E	SS050E	-	PPE050A ¹	NGE050A
20	250	ALDC075E	BR075E	SS075E	BRSS075E	PPE075A	NGE075A
25	250	ALDC100E	BR100E	SS100E	BRSS100E	PPE100A	NGE100A
32	250	ALDC125E	BR125E	SS125E	BRSS125E	PPE125A	NGE125A
40	250	ALDC150E	BR150E	SS150E	BRSS150E	PPE150A	NGE150A
50	250	ALDC200E	BR200E	SS200E	BRSS200E	PPE200A	NGE200A
65	150	ALDEC50E	BR250E	SS250E	BRSS250E	-	-
75	125	ALDC300E	BR300E	SS300E	BRSS300E	PPE300A	NGE300A
100	100	ALDC400E	BR400E	SS400E	BRSS400E	PPE400A	NGE400A
125	75	ALDC500E	BR500E	SS500E	-	-	-
150	75	ALDC600E	BR600E	SS600E	-	-	-

Dixon™ Premium Type F Adaptor x Male BSP



Size (mm)	Working Pressure (psi)	Part Numbers					
		Aluminium	Bronze	Stainless Steel	Brass	Polypropylene	Nyglass
15	150	ALDC050F	BR050F	SS050F	-	PPF050A ¹	NGF050A
20	250	ALDC075F	BR075F	SS075F	BRSS075F	PPF075A	NGF075A
25	250	ALDC100F	BR100F	SS100F	BRSS100F	PPF100A	NGF100A
32	250	ALDC125F	BR125F	SS125F	BRSS125F	PPF125A	NGF125A
40	250	ALDC150F	BR150F	SS150F	BRSS150F	PPF150A	NGF150A
50	250	ALDC200F	BR200F	SS200F	BRSS200F	PPF200A	NGF200A
65	150	ALDC250F	BR250F	SS250F	BRSS250F	-	-
75	125	ALDC300F	BR300F	SS300F	BRSS300F	PPF300A	NGF300A
100	100	ALDC400F	BR400F	SS400F	BRSS400F	PPF400A	NGF400A
125	75	ALDC500F	BR500F	SS500F	-	-	-
150	75	ALDC600F	BR600F	SS600F	-	-	-



- Under no circumstances should camlock couplings be used in compressed air or steam applications
- Polypropylene and nyglass should not be mixed with aluminium fittings