Duo Wafer Stainless Steel Check Valves

Application

- Used for water, oil, and chemicals that can be handled by 316 stainless steel and FKM elastomer seat.

Features

- Suits universal flanges

End Connection

- Suits Tables D/E, ANSI 150/300, DIN PN10 to PN40

Material

- Body: 316 stainless steel
- Disc and spring: 316 stainless steel

Working Pressure

- 580 PSI (40 bar)

Size		Part Numbers
mm	inch	
50	2	DUO316-050
65	2½	DUO316-065
80	3	DUO316-080
100	4	DUO316-100
150	6	DUO316-150
200	8	DUO316-200
250	10	DUO316-250
300	12	DUO316-300

Product Group: VS02

Bronze Swing Check Valves

Application

- Used for general hydraulic, mechanical services and fire protection.

Features

- Can be used in either vertical or horizontal pipelines

End Connection

- Screwed female BSP

Material

- Body: bronze

Temperature/Working Pressure

- Temperature: max. 99°C
- Working pressure: 290 PSI (20 bar) for water, oil and gas

Approved Bronze Swing Check Valves

Size		Part Numbers
mm	inch	
12	½	VC-4B-015
20	¾	VC-4B-020
25	1	VC-4B-025
32	1¼	VC-4B-032
40	1½	VC-4B-040
50	2	VC-4B-050
80	3	VC-4B-080
100	4	VC-4B-100

Product Group: VB11

Standard Bronze Swing Check Valves

Size		Part Numbers
mm	inch	
50	2	VC-4B-50MM
100	4	VC-4B-100MM

Product Group: VB11