



Minsup® Ground Joints

Application

- The Minsup® Ground Joint is an all-purpose coupling. The spud part of the connection is usually fixed to the plant. The nut and tail are assembled onto a hose with a suitable clamp. The two halves are connected or disconnected by rotating the wing nut on the spud.

Materials

- SG Iron ISO 1083-400-250-15
- Zinc plated to AS1789

Thread Designation


- Wing nut is 8" TPI
- BSP tapered male to ISO 7-1
- BSP parallel female to ISO 7-1



Female Spud BSP

Size (mm)	Nominal Bore ID (inch)	Part Number	Box Quantity
50	2	08/014/02/002	20

Product Group: AC02



Double Spud BSP

Size (mm)	Nominal Bore ID (inch)	Part Number	Box Quantity
50	2	08/014/02/004	20

Product Group: AC02



Male Spud BSP

Size (mm)	Nominal Bore ID (inch)	Part Number	Box Quantity
50	2	08/014/02/005	20

Product Group: AC02



Wing Nut

Size (mm)	Nominal Bore ID (inch)	Part Number	Box Quantity
50	2	08/014/02/007	20

Product Group: AC02



Hose Tail

Size (mm)	Nominal Bore ID (inch)	Part Number	Box Quantity
50	2	08/014/02/008	20

Designed to be used with Minsup® clamp 08/023/03/000 - page 138

Product Group: AC02



Cor-O-Zig Tail

Size (mm)	Nominal Bore ID (inch)	Part Number	Box Quantity
50	2	08/014/02/009	20

Designed to be used with Boss™ clamps - page 148

Product Group: AC02