Industrial Hose - Water & Non-Corrosive Liquids (PVC)

White Washdown Delivery Hose (H060)

Applications

- Designed with superior flexibility and crafted from premium PVC, this hose is specifically tailored for low-pressure, cold-water delivery, making it an ideal choice for washdown purposes. In settings such as dairies, abattoirs, and marine environments. It also serves exceptionally well for general watering tasks in parks, sports fields, and gardens.

Features

- UV stabilised
- Abrasion resistant
- Extruded

Hose Construction

- Tube: PVC - blue
- Cover: PVC smooth - white
- Reinforcement: polyester yarn

Temperature

- -5°C to 60°C



Dimensions (mm)		Part Numbers		Pressures				Bend Radius (mm)	Weight (kg/mtr)
				Working		Burst			
ID	OD	Coil 20m	Coil 100m	PSI	Bar	PSI	Bar		
12.7	19.0	H0601220	H06012100	150	10	600	40	150	0.22
19.1	27.0	H0602020	H06020100	150	10	600	40	240	0.41
25.4	34.0	H0602520	H06025100	150	10	600	40	300	0.56
31.8	43.0	H0603220	H06032100	150	10	600	40	380	0.90
38.1	50.5	H0604020	H06040100	150	10	600	40	480	1.00

Product Code: DA05

Fire Reel Hose (H080)

Applications

- Designed with excellent flexibility, UV resistance, and self-extinguishing capabilities, this product is manufactured in accordance with AS/NZS 1221:1997 standards, specifically tailored for utilisation on fire reels.

Features

- UV stabilised
- Abrasion resistant
- Self extinguishing properties

Standards

- Conforms to AS/NZS 1221:1997

Hose Construction

- Tube: PVC - black
- Cover: PVC ribbed - black
- Reinforcement: polyester yarn

Temperature

- -5°C to 60°C



Dimensions (mm)		Part Numbers			Working Pressure		Bend Radius (mm)	Weight (kg/mtr)
ID	OD	Coil 20m	Coil 36m	Coil 100m	PSI	Bar		
19.1	26.0	H0802020	H0802036	H08020100	145	10	228	0.37
25.4	33.0	H0802520	H0802536	H08025100	145	10	300	0.55

Product Group: DA06