

Yellow Spiral ABR PVC Suction Hose (AUSYTAR)

Applications

- A robust suction and discharge hose well suited for use in harsh environments. Especially well suited for use with abrasive slurries, waste and many chemicals in vacuum truck applications.

Features

- Abrasion resistant
- Ozone and weather resistant
- Extruded

Hose Construction

- Tube: PVC/NBR blend - black
- Cover: black and yellow
- Reinforcing: exposed rigid PVC helix - yellow

Temperature

- 5°C to +60°C

Dimensions (mm)		Part Numbers	Pressures				Vacuum (bar)	Bend Radius (mm)	Weight (kg/mtr)
			Working		Burst				
ID	OD	Coil 20m	psi	bar	psi	bar			
50.8	63.4	AUS050YTAR020	73	5.0	146	10.0	1.0	350	1.10
63.5	79.6	AUS065YTAR020	58	4.0	116	8.0	1.0	380	1.50
76.2	93.4	AUS076YTAR020	58	4.0	116	8.0	1.0	400	1.80
101.6	118.0	AUS100YTAR020	43	3.0	86	6.0	1.0	600	2.90



Petrol & Oil Suction/Delivery Hose (AUSBHD)

Applications

- Heavy-duty suction and delivery of oils, oil slurry, grease, diesel fuel, light chemicals and lubricants. Particularly suited for liquid waste transfer, grease trap and septic tank cleaning applications.

Features

- Abrasion resistant
- Oil mist resistant
- High impact resistance
- UV stabilised
- Extruded

Hose Construction

- Tube: smooth PVC/NBR blend - blue
- Reinforcing: rigid PVC embedded helix - blue
- Cover: smooth PVC/NBR blend, smooth - blue

Temperature

- 40°C to 65°C

Dimensions (mm)		Part Numbers		Working Pressure		Vacuum (bar)	Bend Radius (mm)	Weight (kg/mtr)
ID	OD	Cut Length	Coil 20m	psi	bar			
25.4	31.5	-	AUS025BHD020	90	6	1.0	75	0.39
31.8	39.1	-	AUS032BHD020	80	5.5	1.0	105	0.51
38.1	46.2	-	AUS040BHD020	75	5	1.0	155	0.65
50.8	60.7	AUS050BHD	AUS050BHD020	75	5	1.0	205	1.10
63.5	74.4	AUS065BHD	AUS065BHD020	75	5	1.0	255	1.50
76.2	87.1	AUS076BHD	AUS076BHD020	60	4	1.0	305	1.80
101.6	115.1	AUS100BHD	AUS100BHD020	50	3.5	1.0	380	3.00
152.4	169.4	AUS150BHD	AUS150BHD020	30	2	1.0	635	5.51

Cut length available in 10m increments

