

Industrial Hose - Compressed Air (Rubber)

Contractors Yellow Air Hose (A102)

Applications

- Crafted with a smooth yellow non-marking cover to enhance visibility, this cost-effective pneumatic air and water hose is tailored for diverse applications in construction, industrial, and agricultural fields. It's particularly well-suited for heavy-duty air compressor usage, seamlessly supporting a wide range of pneumatic equipment such as portable compressors, jackhammers, breakers, and stampers.

Features

- Ozone resistant
- Weather resistant
- Oil mist resistant
- Abrasion resistant
- Extruded

Hose Construction

- Tube: SBR blend - black
- Cover: SBR blend, smooth - yellow
- Reinforcement - 2 & 4 spiral polyester yarn

Temperature

- -25°C to 75°C



Dimensions (mm)		Part Numbers		Working Pressure		Bend Radius (mm)	Weight (kg/mtr)
ID	OD	Coil 20m	Coil 100m	PSI	Bar		
12.7	21.0	A10201220	A102012100	200	14	100	0.39
19.1	31.0	A10202020	A102020100	200	14	155	0.83
25.4	37.0	A10202025	A102025100	200	14	205	0.92

Product Group: DB43

Contractors Yellow Air Hose - Assembly (A102)

Applications

- Economical general purpose air hose assembly. Abrasive, heat, and ozone resistant. Construction and industrial sites, general maintenance.



Dimensions (mm)		Part Numbers	Working Pressure		Length (mtr)	Description
ID	OD		PSI	Bar		
19.1	31.0	A10202020F	200	14	20	Minsup® A-Type & safety claw clamps
25.4	37.0	A10202520F	200	14	20	Minsup® A-Type & safety claw clamps

Also available with Minsup® Surelock® fittings

Product Group: DB43

Contractors Yellow Air Hose - Whip Hose Assembly (A102)

Applications

- For use on constant vibration pneumatic tools (air drills, pavement breakers, etc.). The heat-treated steel nipple which is connected to the tool withstands vibration and impact for a longer period.
- Connect the other end of the whip hose to the air supply with the quick-acting coupling. The whip hose should remain permanently connected to the tool and should be the same diameter as the supply line hose. Often used in the hire market, construction, road construction, and heavy engineering.



Dimensions (mm)		Part Numbers	Working Pressure		Length (mm)	Description
ID	OD		PSI	Bar		
12.7	21.0	WH15	200	14	600	Minsup® A-Type & safety claw clamps
19.1	31.0	WH20	200	14	600	Minsup® A-Type & safety claw clamps
25.4	37.0	WH25	200	14	600	Minsup® A-Type & safety claw clamps

Also available with Minsup® Surelock® fittings

Product Group: DB43