

Food, Milk & Beverage Suction/Delivery Hose (A635)

Applications

- Highly flexible spiral-reinforced hose designed for managing the transportation and transfer of milk, loading and unloading tankers, dairy unloading bays and equipment within processing and filling facilities. This versatile hose is also suitable for conveying alcoholic beverages containing up to 36% alcohol content including beer, wine and cider, along with a variety of additional liquid food products, including soft drinks, fruit juices, and potable water.

Features

- Food grade FDA approved
- Abrasion resistant
- Weather resistant
- Ozone resistant
- Mandrel built

Hose Construction

- Tube: NR food grade - white
- Cover: NR blend, smooth (wrapped finish) - blue
- Reinforcement: high tensile synthetic textile cords, with double embedded steel wire helix

Temperature

- 40°C to 95°C
- Steam cleaning without pressure up to 130°C/max. 30 min.

Dimensions (mm)		Part Numbers		Pressures			Vacuum (Bar)	Bend Radius (mm)	Weight (kg/mtr)
				Working		Burst			
ID	OD	Cut Length	Coil 20m	PSI	Bar	PSI			
19.1	30.0	A635020	A635020020	90	6	270	0.9	50	0.65
25.4	36.0	A635025	A635025020	90	6	270	0.9	50	0.70
31.8	43.0	A635032	A635032020	90	6	270	0.9	65	0.80
38.1	49.0	A635040	A635040020	90	6	270	0.9	80	1.20
50.8	63.0	A635050	A635050020	90	6	270	0.9	105	1.80
63.5	75.0	A635065	A635065020	90	6	270	0.9	130	2.20
76.2	90.0	A635080	A635080020	90	6	270	0.9	155	3.10
101.6	115.0	A635100	A635100020	90	6	270	0.9	350	3.70

Product Code: DB36



Food & Beverage Suction/Delivery Hose (A625)

Applications

- Premium quality flexible suction and discharge hose featuring a crush-resistant PE helix and high-temperature resistant Chlorobutyl rubber tube, ideal for the transfer of beverages containing up to 96% alcohol content including beer and wine, also suitable for many other beverages and foodstuffs including soft drinks, fruit juices and potable water.

Features

- Food grade FDA approved
- Crush resistant PET helix
- Abrasion resistant
- Weather & ozone resistant
- Mandrel built

Hose Construction

- Tube: IIR Butyl food grade - white
- Cover: smooth (wrapped finish) EPDM blend - red
- Reinforcement: high tensile synthetic textile cords, embedded PET helix

Temperature

- 40°C to 120°C
- Steam cleaning without pressure up to 140°C/max. 30 min.

Dimensions (mm)		Part Numbers		Pressures			Vacuum (Bar)	Bend Radius (mm)	Weight (kg/mtr)
				Working		Burst			
ID	OD	Cut Length	Coil 20m	PSI	Bar	PSI			
25.4	37.0	A625025	A625025020	150	10	450	0.9	115	0.90
31.8	44.0	A625032	A625032020	150	10	450	0.9	145	1.19
38.1	52.0	A625040	A625040020	150	10	450	0.9	180	1.57
50.8	65.0	A625050	A625050020	150	10	450	0.9	245	1.91
63.5	79.5	A625065	A625065020	150	10	450	0.9	310	2.82
76.2	93.0	A625080	A625080020	150	10	450	0.9	390	3.45
101.6	120.0	A625100	A625100020	150	10	450	0.9	555	4.89

Product Code: DB36

