

Industrial Hose - Steam & Hot Water (Rubber)

Hot Water Washdown (A225)

Applications

- Designed specifically for delivery of hot water for washdown applications in food processing facilities, packing houses, bottling plants, breweries and dairies where FDA hose compliance is required.

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant

Hose Construction

- Tube: NBR - white
- Cover: smooth NBR - white
- Reinforcement: polyester yarn

Temperature

- 20°C to 90°C



Dimensions (mm)		Part Numbers			Pressures				Bend Radius (mm)	Weight (kg/mtr)
					Working		Burst			
ID	OD	Cut Length	Coil 20m	Coil 100m	PSI	Bar	PSI	Bar		
12.7	21.9	A225012	A225012020	A225012100	300	20	900	60	100	0.47
19.1	30.2	A225020	A225012020	A225020100	300	20	900	60	155	0.65
25.4	38.0	A225025	A225012520	A225025100	300	20	900	60	205	0.97

Product Code: DB29

FDA Hot Water Washdown (A226)

Applications

- Designed specifically for delivery of hot water for washdown applications in food processing facilities, packing houses, bottling plants, breweries and dairies.

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant
- FDA approved food grade compound

Hose Construction

- Tube: NBR - white
- Cover: smooth NBR - blue
- Reinforcement: polyester yarn

Temperature

- 20°C to 90°C



Dimensions (mm)		Part Numbers			Pressures				Bend Radius (mm)	Weight (kg/mtr)
					Working		Burst			
ID	OD	Cut Length	Coil 20m	Coil 120m	PSI	Bar	PSI	Bar		
12.7	21.9	A226012	A226012020	A226012120	300	20	900	60	100	0.47
19.1	30.2	A226020	A226012020	A226020120	300	20	900	60	155	0.65
25.4	38.0	A226025	A226012520	A226025120	300	20	900	60	205	0.97

Product Code: DB29