

Industrial Hose - Welding & Gas (Rubber)

Single LPG (A110)

Applications

- Designed to fulfill AS/NZS1869 Class C specifications, guaranteeing the safe transfer of LPG for welding, cutting and allied processes across diverse industrial sectors.

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant
- Pinpricked cover
- Extruded

Hose Construction

- Tube: NBR/PVC blend - black
- Cover: NBR/PVC, smooth - orange
- Reinforcement: polyester yarn

Temperature

- 20°C to 70°C

Standards

- AS/NZS1869 Class C



Dimensions (mm)		Part Numbers			Pressures				Bend Radius (mm)	Weight (kg/mtr)
					Working		Burst			
ID	OD	Cut Length	Coil 20m	Coil 100m	PSI	Bar	PSI	Bar		
4.8	13.0	A11005	A11005020	A11005100	375	25	1500	100	40	0.18
6.4	14.0	A11006	A11006020	A11006100	375	25	1500	100	50	0.19
9.5	18.0	A11010	A11010020	A11010100	375	25	1500	100	75	0.29

Product Code: DB23

Divers/Air Breathers (H100)

Applications

- Designed with excellent flexibility and durability, this product is manufactured in accordance with AS/NZS 2299.1 & AS/NZS 1716 standards, approved for use in professional and sports air-breathing apparatus.

Features

- UV stabilised
- Abrasion resistant
- FDA approved

Hose Construction

- Tube: PVC - white
- Cover: PVC, smooth - yellow
- Reinforcement: polyester yarn

Temperature

- 5°C to 60°C

Standards

- AS/NZS 2299.1 & AS/NZS 1716



Dimensions (mm)		Part Numbers		Pressures				Bend Radius (mm)	Weight (kg/mtr)
				Working		Burst			
ID	OD	Coil 20m	Coil 100m	PSI	Bar	PSI	Bar		
7.9	15.0	H1000820	H10008100	350	24	1400	96	95	0.15
9.5	17.5	H1001020	H10010100	350	24	1400	96	120	0.18

Product Code: DA08