

Neoprene Insertion Sheet Rubber

Application

- Neoprene rubber sheet is a preferable choice of rubber sheeting when exposed to the weather. This product also has a moderate resistance to petroleum based fluids. Neoprene rubber sheeting is used for many applications, including gasket making, matting, baffles & bumper strips.

Specifications

- Reinforcing: nylon ply
- Tensile strength: 40±5 kg/cm²
- Hardness: shore - A 65+/-5
- Specific gravity: 1.5±0.05
- Elongation rate: minimum 250%

Material

- CR

Temperature

- 20°C to 60°C

Part Numbers	Thickness (mm)	Length (mtr)	Width (mm)	Weight (kg/10mtr Roll)
NEO015R	1.5	10	1200	27
NEO030R	3.0	10	1200	54
NEO045R	4.5	10	1200	81
NEO060R	6.0	10	1200	108

Product Group: DB27



Skirting Sheet Rubber

Application

- Skirting rubber is a sheeting applied to the sides of conveyor belst to prevent loss of material travelling on the conveyor.

Specifications

- Tensile strength: 40±5 kg/cm²
- Hardness: shore - A 65+/-5
- Specific gravity: 1.5±0.05
- Elongation rate: minimum 250%

Material

- SBR

Temperature

- 20°C to 60°C

Part Numbers	Thickness (mm)	Length (mtr)	Width (mm)	Weight (kg/30mtr Roll)
SIR060200	6	30	200	54.00
SIR100100	10	30	100	45.00
SIR100150	10	30	150	67.50
SIR100200	10	30	200	90.00
SIR100250	10	30	250	112.50
SIR120100	12	30	100	54.00
SIR120125	12	30	125	67.50
SIR120150	12	30	150	81.00
SIR120200	12	30	200	108.00
SIR120300	12	30	300	162.00
SIR160100	16	30	100	72.00
SIR160150	16	30	150	108.00
SIR160200	16	30	200	144.00
SIR160250	16	30	250	180.00
SIR190100	19	30	100	85.50
SIR190150	19	30	150	128.25
SIR190200	19	30	200	171.00
SIR190350	19	30	350	300.00

Product Group: DB27

