

Stainless Steel Ball Valve - Three Piece - Electric Actuator

Application

- For use with air, water, oil, gas, and most chemicals that are compatible with body and trim.

Design

- 3-piece
- Full bore
- 240AC actuator open/shut

Material

- Valve body: 316 stainless steel
- Actuator body: hard anodised aluminium - IP67
- Seat: PTFE

End Connection

- Female BSP

Available Options

- 110V AC, 24V AC, 24V DC

Size		Part Numbers
mm	inch	
12	½	SS3P015-EA
20	¾	SS3P020-EA
25	1	SS3P025-EA
32	1¼	SS3P032-EA
40	1½	SS3P040-EA
50	2	SS3P050-EA
65	2½	SS3P065-EA
80	3	SS3P080-EA
100	4	SS3P100-EA

Product Group: VS02



Three Way Stainless Steel Ball Valve - L & T Port

Application

- For use with air, water, oil and gas and most chemicals that are compatible with body and trim.

Design

- Lever operated
- Locking device
- Blow-out proof stem
- ISO 5211 mounting

Material

- Body: 316 stainless steel (ASTM A351 CF8M)
- Ball: 316 stainless steel (ASTM A351 CF8M)
- Seat: PTFE

End Connection

- Female BSP

Working Pressure

- 1000 PSI (69 bar)

Approvals

- Watermark

Size		Part Numbers	
mm	inch	L port	T port
12	½	SS3WL012	SS3WT012
20	¾	SS3WL020	SS3WT020
25	1	SS3WL025	SS3WT025
32	1¼	SS3WL032	SS3WT032
40	1½	SS3WL040	SS3WT040
50	2	SS3WL050	SS3WT050

Product Group: AR02

