

Composite Scroll Tail Series

Applications

- Spiral camlock fittings and ferrules are for use with the composite hose to suit the pitch of the wires on the hose. Ideal for a wide variety of applications including, water, oil/fuel, powders, and adhesives. Nitrile Buna-N rubber seals are standard.



Size		Part Numbers			
		Type C Coupler x Hose Tail		Type E Adaptor x Hose Tail	
mm	inch	Aluminium	Stainless Steel	Aluminium	Stainless Steel
40	1½	STC040AL	STC040SS	STE040AL	STE040SS
50	2	STC050AL	STC050SS	STE050AL	STE050SS
65	2½	STC065AL	STC065SS	STE065AL	STE065SS
80	3	STC080AL	STC080SS	STE080AL	STE080SS
100	4	STC100AL	STC100SS	STE100AL	STE100SS

Refer to Section C Camlock Accessories for spare parts - page 106

Product Group: BB06



Size		Part Numbers		
		Type C Coupler x Hose Tail	Type E Adaptor x Hose Tail	Type C Coupler x 68° Hose Tail
mm	inch			
40	1½	STC150AL	STE150AL	-
50	2	STC200AL	STE200AL	-
65	2½	STC250AL	STE250AL	-
80	3	STC300AL	STE300AL	STC30068AL
100	4	STC400AL	STE300AL	STC40068AL

Product Group: BB06

Vapour Recovery Coupler



Size		Part Number
mm	inch	
100	4	VRST400

Product Group: BB06

Scroll Tail Crimp Stems - Buttweld



Size		Part Numbers
mm	inch	
150	6	STW0150CS
200	8	STW0200CS

Product Group: BB06