

Stretch Straps

Application

- A durable tie down strap.

Material

- Straps are EPDM
- S-hooks are steel



- Do not exceed the maximum safe stretch
- Inspect before each use
- Do not use if the strap is cut, cracked or abraded
- Inspect hooks for damage and/or wear, and replace them if needed
- Protect strap from sharp edges or heat
- Wear eye protection during use
- Do not use this product as the primary tie down
- Refer to federal or state regulations for proper tie-down methods

Strap Length (mm)	Part Numbers
250	SSE10
380	SSE15
530	SSE21
790	SSE31
1040	SSE41



Product Group: AU02

Self Stick Safety Tape

Application

- Dixon strongly recommends the use of a safety tag or warning label on all hose assemblies. The safety tape reads:

WARNING

- Worn-out hose fittings should be replaced
- Loose clamps on hose can be dangerous
- Bolt type clamps should be retensioned regularly
- For extra safety, retaining devices such as clips, chains or cables must be used

Size		Part Number
Width (mm)	Length (mtrs)	
15	50	DSTW

Approximately 255 warnings

Product Group: AU02



Dixon™ Coupling Lubricant

Features

- Biodegradable lubricant for coupling shanks, O-rings, hoses, sleeves, rubber washers, and grommets
- Once the coupling lubricant dries, the slipping action goes away

Volume (ltr)	Part Numbers
1	DCL20
4	DCL80

Product Group: AU02

