

High Flow Heavy-Duty Hot Washdown Gun

Application

- Suitable for washdown in factories, commercial kitchens or used in any other industrial washdown applications.

Features

- Heavy duty washdown gun
- Built-in BSP swivel inlet
- Flow rate at 300 PSI is 60 lt/min
- Maximum temperature 90°C
- Maximum operating pressure 350 PSI

Thread

- Built-in ½" BSP swivel inlet

Size		Part Number	Inlet Thread
mm	inch		
15	½	HDBWG050A	BSP

Product Group: AT01



Flow Boss™ Heavy-Duty Washdown Gun

Application

- For low-pressure cleaning and sanitation applications, such as food and dairy processing, tank and drum cleaning, pharmaceutical and chemical manufacturing, and meat and poultry packing.

Features

- Insulated covers for heat protection
- All stainless steel and brass construction for superior corrosion resistance
- Flow indication arrow and arrest clip
- Hollow cone spray pattern
- New improved design with the high flow rate
- Increased strength and durability
- Complete serviceability
- An upgraded seal design for superior pressure tightness.
- Hose connects at the base of the gun for easy maneuvering
- Ergonomic design for operator comfort. ½" BSP female inlet

Specifications

- Flow capacity: 57 lpm at 500kpa/72 PSI
- Maximum operating pressure: 2400 kpa/350 PSI

Colour

- Blue rubber cover

Temperature

- Rubber-coated handle protects hands from water temperatures to 80°C

Thread

- 12 mm (½") BSP female

Size		Part Number	Inlet Thread
mm	inch		
12	½	DWG050A	BSP

Product Group: AT01



Pistol-Grip Water Nozzle

Features

- Heavy-duty all zinc metallised body
- All brass valve stem and adjusting nut
- Stainless steel spring with lifetime packing
- Clip locks to any spray pattern

Pressures

- Maximum 620 kPa/90 PSI
- Maximum flow rate: 23 l/m

Thread

- Inlet (handle): 20mm (¾") BSP female

Size		Part Number	Inlet Thread
mm	inch		
20	¾	CSN75A	GHT

Product Group: AT01



- Do not use these products with steam lines