

Cutting-off wheel

A 24 EXTRA



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□□
Aggression	■■■■■□□□
Service life	■■■■■□□□

Product benefit

Proven a million times over - Standard wheel with outstanding price-performance ratio - For universal use in metalworking - Fast cutting off of solid material

Materials

Metals ●

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	242137
125 x 2,5 x 22,23		80 m/s	12250 rpm	25	328771
125 x 2,5 x 22,23		80 m/s	12250 rpm	25	328774
180 x 3 x 22,23		80 m/s	8500 rpm	25	328765
230 x 3 x 22,23		80 m/s	6650 rpm	25	328761
230 x 3 x 22,23		80 m/s	6650 rpm	25	328763

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

