


Abrasive cloth, multibond

CS 410 X



Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Close
Backing	X-cotton

Product benefit

Tear-resistant cloth with reinforced backing - Spiral shaped joint, cylindrical form - Cool grinding and no heat tinting due to additional multibond - Increased abrasive performance for use on stainless steel - High aggressiveness when used with rubber drum GK 555

Materials

Stainless steel	●
NF metals	○

Applications

- Apparatus and container manufacturing
- Railing construction
- Stainless steel processing industry

Available grits:

16	20	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000	4000	5000	6000
----	----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------	------	------

Diameter x Width in mm	grain	type of coat.abras.	Packing unit/pcs.	Cat. number
25 x 25	40	CS 410 X	50	324117
25 x 25	60	CS 410 X	50	324118
25 x 25	80	CS 410 X	50	328368
25 x 25	120	CS 410 X	50	328367
38 x 25	40	CS 410 X	50	324119
38 x 25	60	CS 410 X	50	324121

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

