


Combi non-woven web spindle mop

NCS 600



Properties

Bonding agent	Resin
Grain	Aluminium oxide

Product benefit

High removal rate and fine surface scratch pattern due to combination of non-woven and abrasive cloth flaps - Long service life

Materials

Stainless steel	●
Metals	●
Plastic	⦿

Applications

- Stainless steel processing industry
- Apparatus and container manufacturing

Diameter x Width x Shaft in mm	grain	Grade	Colour	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
50 x 30 x 6	60	coarse	maroon	32 m/s	12200 rpm	10	258932
50 x 30 x 6	100	medium	maroon	32 m/s	12200 rpm	10	258933
60 x 30 x 6	60	coarse	maroon	32 m/s	10200 rpm	10	258936
60 x 30 x 6	100	medium	maroon	32 m/s	10200 rpm	10	258937
80 x 50 x 6	60	coarse	maroon	32 m/s	7600 rpm	10	258944
80 x 50 x 6	100	medium	maroon	32 m/s	7600 rpm	10	258945

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

