

50090**Piusi 240V High Flow Diesel Fuel Bowser 90L/min**

August 2026

The 50090 240V High Flow Diesel Fuel Bowser from Piusi is designed & manufactured in Italy for non-commercial use and its sturdy structure allows fixing to walls, tanks, drums & even its own pedestal*.

Capable of flow rates of up to 90L/min the 50090 bowser is supplied standard with an automatic nozzle with swivel connection and four metres of 1" diesel fuel hose.

The pump at the heart of the 50090 is a self-priming vane type pump fitted with a bypass & is installed on anti-vibration supports, effectively prolonging service life. A nutating disk displacement flow meter with 4-digit mechanical readout system is extremely accurate and reliable.

A compact & space saving design incorporates an integrated nozzle holder with stop/start pump lever, intake mesh filter and an induction motor that is fitted with thermal motor overload protection.

The 50090 240V High Flow Diesel Fuel Bowser is a significant and sought after new addition to the premium Alemlube bowser range.

SPECIFICATIONS, FEATURES & BENEFITS

- Automatic nozzle with flow rates of up to 90L/min
- Self-priming vane type pump
- Induction motor fitted with thermal motor overload protection
- Intake mesh filter
- Mechanical 4 digit meter accurate to $\pm 1.0\%$
- IP55 Rating
- 700 watt
- 4.9amp maximum
- Noise level below 75dB
- 1" diesel fuel hose length of 4m

Also available:

- 50090P** 240V Diesel Fuel Bowser 90L/min with Pedestal
- 50070** 240V Diesel Fuel Bowser 70L/min
- 5070P** 240V Diesel Fuel Bowser 70L/min with Pedestal

* The pedestal is available for a free standing mini bowser type application, and is included only in 50090P.