



4 Point Heavy Duty Pulleys

Provide long life under demanding conditions. They are installed with standard 1/2" or 5/8" bolts. Applications include agricultural, power transmission equipment, and conveyor systems. Aetna V-belt idlers are generally used as tensioners or direction changers. Permanently lubricated and sealed against grime and dirt. Fit into existing designs with little or no engineering changes, or are readily adapted to new designs.

ADVANTAGES

- Over-size, factory packed lubricant chamber assures maximum life and operating efficiency without troublesome relubrication
- Case hardened to resist belt abrasion
- Available for most common V-belt sizes
- Bearing races are hardened to resist wear, outers and inners are accurately formed for smooth running
- Aetna's self-contouring, free-running, self-wiping seal provides positive contact under all conditions of misalignment
- Full ball complement for high durability

Flat Single Flange Idlers



PART NO.	UNIT	A	B	C	D	E	F	G	H	WEIGHT (LBS)
AG2365-1AM*	Inch	.516/.522	1-3/16	2-3/4	3-1/2	1-1/2	1-11/16	.190	1.125	1.03
	mm	13.106/13.258	30.162	69.85	88.9	38.1	42.862	4.826	28.575	0.467
AG2365-A	Inch	.516/.522	1-3/16	2-3/4	3-1/2	1-1/2	1-11/16	.190	1.125	1.03
	mm	13.106/13.258	30.162	69.85	88.9	38.1	42.862	4.826	28.575	0.467

**Includes Felt & Slinger Seals*