




SA, SA-F, NA
Cylindrical bore
(with eccentric locking collar)
d 65 ~ 75 mm



Shaft Dia		Dimensions										Basic Load Ratings		Factor	Bearing No.		Dimensions								Set Screw Brg.Bore		Mass
mm	inch	<i>D</i>		<i>B</i>		<i>B</i> ₁		<i>C</i>		<i>r</i> (min.)		<i>C</i> _r <i>C</i> _{0r}		<i>f</i> ₀			<i>C</i> ₁	<i>S</i>		<i>S</i> ₂		<i>d</i> ₁				kg	
		mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch				mm	inch	mm	inch	mm	inch	mm				inch
65	2 1/2	120	4.724	68.2	2.685	85.7	3.374	28	1.102	1.5	0.059	57.2	40.1	14.4		NA213-40	7.5	0.295	34.1	1.343	8.5	0.335	92	3.622	–	3/8-24UNF	2.51
		120	4.724	68.2	2.685	85.7	3.374	28	1.102	1.5	0.059	57.2	40.1	14.4		NA213	7.5	0.295	34.1	1.343	8.5	0.335	92	3.622	M10x1.25	–	2.45
70	2 11/16	150	5.906	68.3	2.689	92.1	3.626	40	1.575	2.1	0.083	104	68.2	13.2		NA314-43	12.5	0.492	34.1	1.343	11.9	0.469	101.6	4.000	–	1/2-20UNF	4.7
	2 3/4	125	4.921	68.2	2.685	85.7	3.374	30	1.181	1.5	0.059	62.2	44.1	14.5		NA214-44	9	0.354	34.1	1.343	8.5	0.335	97	3.819	–	3/8-24UNF	2.94
		125	4.921	68.2	2.685	85.7	3.374	30	1.181	1.5	0.059	62.2	44.1	14.5		NA214	9	0.354	34.1	1.343	8.5	0.335	97	3.819	M10x1.25	–	2.92
75	2 15/16	160	6.299	74.6	2.937	100	3.937	42	1.654	2.1	0.083	113	77.2	13.2		NA315-47	14.5	0.571	37.3	1.469	12.7	0.500	112.7	4.437	–	5/8-18UNF	5.8
	3	130	5.118	74.6	2.937	92.1	3.626	32	1.260	1.5	0.059	67.4	48.3	14.5		NA215	9	0.354	37.3	1.469	8.5	0.335	102	4.016	M10x1.25	–	2.74
		130	5.118	74.6	2.937	92.1	3.626	32	1.260	1.5	0.059	67.4	48.3	14.5		NA215-48	9	0.354	37.3	1.469	8.5	0.335	102	4.016	–	3/8-24UNF	2.72