Designed with aluminim oxide grain, the depressed centre shape allows for a lower cutting angle so the angle grinder can get closer to the material.

Depressed centre wheels may also be referred to as raised hub wheels.





Fast Cut - Cutting (Type 42 Depressed Centre)

- A24/30T - Medium/Coarse Aluminium oxide grain hard grade
- Fast cut reinforced depressed centre wheel for cutting off
- For steel and hard ferrous metals
- Durable resin bond designed for fast cut while retaining excellent wheel life
- suitable for notching

90°

Structural steel, sheet metal and ferrous metals

METAL

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
125 x 3.4 x 22.23	12,250	100	66252841679	9314188060277	"High performance general purpose wheel"
180 x 3.4 x 22.23	8,500	50	66252841685	9314188060536	



Fast Cut - Cutting (Type 42 Depressed Centre)

- A30S - Medium grit Aluminium oxide grain medium grade
- Fast cut reinforced depressed centre wheel for cutting off
- For steel and hard ferrous metals
- Durable resin bond designed for fast cut while retaining excellent wheel life
- suitable for notching

90°

Structural steel, sheet metal and ferrous metals

METAL

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
100 x 3.4 x 16.00	15,300	100	66252841702	9314188063179	"High performance general purpose wheel"
115 x 3.4 x 22.23	13,300	100	66252841707	9314188063308	



Fast Cut - Cutting (Type 42 Depressed Centre)

- A24/30T - Medium/Coarse Aluminium oxide grain hard grade
- Fast cut reinforced depressed centre wheel for cutting off
- For steel and hard ferrous metals
- Durable resin bond designed for fast cut while retaining excellent wheel life
- suitable for notching

90°

Structural steel, sheet metal and ferrous metals

METAL

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
230 x 3.4 x 22.23	6,500	50	66252841691	9314188060703	"High performance general purpose wheel"
230 x 3.4 x 22.23	6,500	50	66252841693*	9314188135166	

* Indicates an extra layer of fibreglass in construction