Designed with a sharp silicon carbide grain for grinding masonry, natural stone, tiles and ceramic.
The formulation resists loading or clogging of the wheel.

The depressed centre design allows the flange/lock nut to recess within the wheel so that it can be used for various grinding applications.

Depressed centre wheels are designed to handle the most severe right angle grinding applications from heavy stock removal to rough blending.

Depressed centre wheels may also be referred to as raised hub wheels.



General Purpose - Iron Free Grinding (Type 27 Depressed Centre)



- C30T Silicon carbide abrasive medium grit, hard grade
- Excellent depressed centre grinding wheel, for fast stock removal
- For dry grinding of brick, concrete, ceramic & stone
- Durable resin bond designed for grinding while retaining excellent wheel life

30°

Brick, concrete ceramic &stone

CONCRETE STONE BRICK

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
100 x 4.0 x 16.00	15,300	50	66252841771	9314188075066	"Ideal for grinding masonry materials"

General Purpose - Iron Free Grinding (Type 27 Depressed Centre)



- C30R Silicon carbide abrasive medium grit, medium grade
- Excellent depressed centre grinding wheel, for fast stock removal
- For dry grinding of brick, concrete, ceramic & stone
- Durable resin bond designed for grinding while retaining excellent wheel life

30°

Brick, concrete ceramic &stone

CONCRETE STONE BRICK

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
100 x 6.0 x 16.00	15,300	50	66252841765	9314188075103	"Ideal for grinding masonry materials"
115 x 6.0 x 22.23	13,300	50	66252841766	9314188075233	
125 x 6.8 x 22.23	12,250	50	66252841767	9314188075363	
180 x 6.8 x 22.23	8,500	25	66252841768	9314188075622	
230 x 6.8 x 22.23	6,250	25	66252841769	9314188075882	