Designed for die grinders, the small diameter cut-off line consists of Type 41 straight wheels from 51mm and 76mm diameters.

These wheels come in ultra thin 0.89mm thickness for quick cutting and minimal material loss.



Ultra Thin - Automotive



- A60T Aluminium oxide grain
- Razor cut reinforced straight wheel for fast cutting off where minimal material loss is desired
- For stainless steel, alloy steels and hard ferrous metals
- Durable resin bond designed for fast cut while retaining excellent wheel life
- Fillers free of Iron

Stainless steel, alloy steels and hard ferrous metals

METAL STAINLESS

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
50 x 0.89 x 9.53	30,600	25	66252841636	9314188002710	"Small diameter wheels for use with die grinders"
76 x 0.89 x 6.35	23,900	25	66252841638	9314188027041	
76 x 0.89 x 9.53	23,900	25	66252841639	9314188027089	

Designed for die grinders, the small diameter cut-off line consists of Type 41 straight wheels from 51mm to 76mm diameters.

These wheels come in fast cut 2.5mm thickness for low material loss on durable applications.



Fast Cut - Automotive



- A30S Aluminium oxide grain
- Fast cut reinforced straight wheel for cutting off
- For stainless steel and hard ferrous metals
- Durable resin bond designed for fast cut while retaining excellent wheel life

Stainless steel, alloy steels and hard ferrous metals

METAL STAINLESS

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
51 x 2.5 x 10.00	24,300	200	66252919937	9314188001027	"Small diameter wheels for use with die grinders"
65 x 2.5 x 10.00	24,300	200	66252919939	9314188001065	
76 x 2.5 x 10.00	19,100	200	66252918968	9314188001102	

Designed with aluminium oxide grain for general purpose fast cutting of metals.

All wheels are reinforced for the demanding nature of cutting-off metals with right angle grinders.





Fast Cutting

- A36S Aluminium oxide grain
- Fast cut reinforced straight wheel for cutting off
- For steel and hard ferrous metals
- Durable resin bond designed for fast cut while retaining excellent wheel life

90°

Metal, Mild Steel

METAL

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
100 x 2.5 x 16.00	15,300	100	66252841558	9314188001287	"High performing general purpose wheel"
115 x 2.5 x 22.23	13,300	100	66252841560	9314188001324	
125 x 2.5 x 16.00	12,250	100	66252920010	9314188001416	
125 x 2.5 x 22.23	12,250	100	66252841561	9314188001454	
180 x 2.5 x 22.23	8,500	50	66252841566	9314188001843	
230 x 2.5 x 22.23	6,650	50	66252841574	9314188002208	
230 x 2.5 x 25.40	6,650	50	66252841576	9314188002246	
230 x 2.5 x 22.23	6,650	50	66252841575	9314188003625	
230 x 3.1 x 22.23	6,650	50	66252841584	9314188003601	

Designed for cutting non ferrous metals like aluminium, brass and copper.

The formulation resists loading or clogging of the wheel.

Aluminium cutting wheels type 41 available from 100mm - 230mm, depressed centre wheel type 42 available in 125mm.





Fast Cutting

- A36S Aluminium oxide grain
- Fast cut reinforced straight wheel for cutting off
- For non ferrous metals such as Aluminium, copper, brass & bronze
- Has a load resistant bond to reduce clogging

90°

Aluminium, copper, brass & bronze

ALUMINIUM

SIZE (mm)	MAX. RPM	PACK QTY	PRODUCT #	BARCODE #	SUMMARY
100 x 2.5 x 16.00	15,300	100	66252841602	9314188005025	"Ideal for cutting aluminium"
115 x 2.5 x 22.23	13,300	100	66252841603	9314188005155	
125 x 2.5 x 22.23	12,250	100	66252841604	9314188005285	
230 x 2.5 x 22.23	6,650	50	66252841606	9314188005674	