


Double Row Ball Bearings

5200-2RS

5300-2RS

Series 5200-2RS



Bearing No.	Dimensions (mm)				Limiting Speed (r.p.m.)	Load Rating (kgf)		Weight (kg)
	Bore	O.D.	Width	Chamfer		Cr	Cor	
5200-2RS	10	30	14.3	1.0	13,000	700	390	0.060
5201-2RS	12	32	15.9	1.0	12,000	900	510	0.070
5202-2RS	15	35	15.9	1.0	10,000	1,150	700	0.080
5203-2RS	17	40	17.5	1.0	9,500	1,300	830	0.090
5204-2RS	20	47	20.6	1.5	8,500	1,900	1,250	0.120
5205-2RS	25	52	20.6	1.5	7,400	2,100	1,450	0.210
5206-2RS	30	62	23.8	1.5	6,000	2,500	1,850	0.290
5207-2RS	35	72	27.0	2.0	5,500	3,100	2,400	0.430
5208-2RS	40	80	30.2	2.0	5,000	3,600	2,880	0.570
5209-2RS	45	85	30.2	2.0	4,500	4,100	3,300	0.620
5210-2RS	50	90	30.2	2.0	4,100	4,300	3,800	0.670
5211-2RS	55	100	33.3	2.5	3,800	5,500	4,600	0.960

RSNR, 2RSNR types are available

Series 5300-2RS

Bearing No.	Dimensions (mm)				Limiting Speed (r.p.m.)	Load Rating (kgf)		Weight (kg)
	Bore	O.D.	Width	Chamfer		Cr	Cor	
5302-2RS	15	42	19.0	1.5	10,000	1,300	830	0.155
5303-2RS	17	47	22.2	1.5	9,000	1,900	1,250	0.190
5304-2RS	20	52	22.2	2.0	8,000	2,000	1,260	0.210
5305-2RS	25	62	25.4	2.0	6,600	2,700	1,800	0.350
5306-2RS	30	72	30.2	2.0	5,500	4,000	2,800	0.550
5307-2RS	35	80	34.9	2.5	5,000	5,100	3,500	0.710
5308-2RS	40	90	36.5	2.5	4,400	5,700	4,200	1.050

RSNR, 2RSNR types are available