# GAUGES

## The sizes, both decimal and metric equivalent, are permanently etched on each blade

| | | 3072 | 3074 | 3075 | 3078 | 3079 |
|---|---|---|---|---|---|---|
| 0.50-in Width | .008" | ● | ● | ● | | ● |
| | .009" | ● | ● | ● | | ● |
| | .010" | ● | ● | ● | | ● |
| | .011" | ● | ● | ● | | ● |
| | .012" | ● | ● | ● | | ● |
| | .013" | ● | ● | ● | | ● |
| | .014" | ● | ● | ● | | ● |
| | .015" | ● | ● | ● | | ● |
| | .016" | ● | ● | ● | | ● |
| | .017" | ● | ● | ● | | ● |
| | .018" | ● | ● | ● | | ● |
| | .019" | ● | ● | ● | | ● |
| | .020" | ● | ● | ● | | ● |
| | .021" | ● | ● | ● | | ● |
| | .022" | ● | ● | ● | | ● |
| | .023" | ● | ● | ● | | ● |
| | .024" | ● | ● | ● | | ● |
| | .025" | ● | ● | ● | | ● |
| | .026" | ● | ● | ● | | ● |
| | .027" | ● | ● | ● | | ● |
| | .028" | ● | ● | ● | | ● |
| | .029" | ● | ● | ● | | ● |
| | .030" | ● | ● | ● | | ● |
| | .019"-.021" | | | | ● | |
| | .022"-.024" | | | | ● | |
| | .025"-.027" | | | | ● | |
| | .031"-.033" | | | | ● | |
| | .058"-.060" | | | | ● | |
| | .063"-.065" | | | | ● | |

### 5469

**DOUBLE-END HANDLE FOR FEELER GAUGE BLADES**



- Color-coded handle makes using the correct blade fast and accurate, where light blue is for intake and red for exhaust
- Even in dimly lit shops, the technician can be confident in using the correct blade without wasting time having to read the blades every time

### 3072

**23-BLD FEELER GAUGE FOR CUMMINS DIESEL VALVE ADJ.**

- 6" blade, with 1" long 90° offset



### 3074

**23-BLD FEELER GAUGE FOR GEN. H.D. TRUCK VALVE ADJ.**

- 3" blade, with 5/8" long 45° offset



### 3075

**23-BLD FEELER GAUGE FOR DETROIT DIESEL VALVE ADJ.**

- 3" blade, with 1" long 30° offset, and 1/2" of 0.002"step



### 3078

**FEELER GAUGE SET, JACOBS ENGINE BRAKES-DETROIT DIESEL**

- Blade sizes and usage: 0.019" - 0.021" Series 60 model years 1999 and before; 0.022" - 0.024" Series 60 all model years, Series 50; 0.025" - 0.027" Series 60 all model years, Series 50; 0.031" - 0.033" Series 60 model year 2000 and after; 0.058" - 0.060" Series 71, Series 92; 0.063" - 0.065" Series 71, Series 92
- This set contains the gauges required to set slave piston lash on Detroit Diesel engines
- 4" blade with 1/2" long 45° offset and 0.002" step Go-No-Go
- 0.002" step is on the bottom side of the blade so that the Go-No-Go can be felt against the exhaust rocker arm adjusting screw or exhaust valve bridge (depending on the model engine)



### 3079

**MASTER FEELER GAUGE SET FOR H.D. TRUCK VALVE ADJ.**



Set contains:
Part No. 5469 - double-end plastic color-coded handle
Part No. 3072 - 6" blade with 1" long 90° offset;
Part No. 3074 - 3" blade with 5/8" long 45° offset
Part No. 3075 - 3" blade with 1" long 30° offset and 1/2" of 0.002" step

- This handle and blade set was designed to make valve adjustments faster and easier