

MSA AND MAGSWITCH LIFTING MAGNETS


MSA Pro-Lift Lifting Magnets

PRO-LIFT LIFTING MAGNET 300KG
CODE: PL300




Max Breakaway:	**900 kg**
Safe Working Load:	**300 kg**
Full Saturation Thickness:	**40 mm**
Max Safe Shear:	**N/A**
Min. Thickness for De-stack:	**40 mm**
Net Weight:	**10 kg**

PRO-LIFT LIFTING MAGNET 500KG
CODE: PL500



Max Breakaway:	**1500 kg**
Safe Working Load:	**500 kg**
Full Saturation Thickness:	**40 mm**
Max Safe Shear:	**N/A**
Min. Thickness for De-stack:	**40 mm**
Net Weight:	**12.5 kg**

PRO-LIFT LIFTING MAGNET 600KG
CODE: PL600



Max Breakaway:	**1800 kg**
Safe Working Load:	**600 kg**
Full Saturation Thickness:	**50 mm**
Max Safe Shear:	**N/A**
Min. Thickness for De-stack:	**50 mm**
Net Weight:	**20 kg**

PRO-LIFT LIFTING MAGNET 1000KG
CODE: PL1000



Max Breakaway:	**3000 kg**
Safe Working Load:	**1000 kg**
Full Saturation Thickness:	**60 mm**
Max Safe Shear:	**N/A**
Min. Thickness for De-stack:	**60 mm**
Net Weight:	**53 kg**

PRO-LIFT LIFTING MAGNET 2000KG
CODE: PL2000



Max Breakaway:	**6000 kg**
Safe Working Load:	**2000 kg**
Full Saturation Thickness:	**70 mm**
Max Safe Shear:	**N/A**
Min. Thickness for De-stack:	**70 mm**
Net Weight:	**80 kg**

PRO-LIFT LIFTING MAGNET 3000KG
CODE: PL3000



Max Breakaway:	**9000 kg**
Safe Working Load:	**3000 kg**
Full Saturation Thickness:	**80 mm**
Max Safe Shear:	**N/A**
Min. Thickness for De-stack:	**80 mm**
Net Weight:	**160 kg**