ASR 35 H ACP (602059190) Vacuum cleaner

Order No. 602059190
EAN 4061792155817



Representative picture



- Especially suited for extracting concrete and rock dust
- Ideal vacuum cleaner for removal of mould and old insulation in roof and wall areas
- Ideal when sanding painted or coated wood surfaces with lead, nickel, cadmium or chromium content
- Compact vacuum cleaner for liquids and dry solids with commercial registration
- Power socket for a power tool for using the automatic start/shut-down of the vacuum cleaner
- AutoCleanPlus: saves both costs and time thanks to automatic MPulse filter cleaning during continuous use
- If the optimum suction performance falls below a certain level, the filters are vibrated immediately
- Maximum user protection: certified in accordance with EU standard for H class dusts
- Automatic shut-down when vacuuming liquids once the maximum fill level is reached
- Warning signal on shortfall of the minimum volume flow to protect the user
- Optimum suction power by preselection of the hose diameter
- Automatic trailing mechanism for emptying the suction hose completely
- Antistatic basic equipment prevents static charge when using appropriate accessories
- Sturdy thanks to especially large wheels and castors with wheel stop
- Cable winding mechanism
- Practical accessory case and storage area

Technical values

KEY FIGURES

Air output max.	4380 l/min / 157 cfm
Vacuum	270 hPa (mbar) / 3.6 psi

Filter surface	8600 cm^2 / 1333 sq.inch
Input power max.	1400 W
Container volume	35 l / 9 gal
Suction hose Ø	35 mm / 1 3/8 "
Hose length	4 m / 15 ft
Weight	16 kg / 35.3 lbs
Cable length	8 m / 26 ft

VIBRATION

Vibration	0.5 m/s^2
Uncertainty of measurement K	1.5 m/s^2

NOISE EMISSION

Sound pressure level	69 dB(A)

Scope of delivery

- Antistatic suction hose (Ø 35 mm / 4 m)
- Connection bush Ø 41/48 mm
- Handle adapter
- 2 Plastic suction tubes
- 2 HEPA polyester filter cassettes
- PE Disposal bag
- Crevice nozzle
- Floor nozzle (300 mm wide)