RFEV 19-125 RT (603826710) Renovation milling machine

Order No. 603826710
EAN 4007430313720



Representative picture

- For effective removal of plaster, adhesive residues, soft screed and old paint from walls, ceilings and floors
- Maximum productivity thanks to top 1,900 Watt with low weight
- Double reduction high-performance gearing for maximum torque and high output
- Fast work progress thanks to large milling diameter
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Cutting depth can be adjusted easily and without the need for tools
- Robust protective cover made from die-cast aluminium with spring-mounted brush rim for low-dust working
- Front handle for safe and uniform guidance when milling, adjustable without tools
- Can be used as renovation grinder on smaller areas when using a diamond cup wheel
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Connection for dust extraction Ø 35/41 mm

Technical values

KEY FIGURES

Working width	125 mm
Cutting depth	0 - 6 mm // 0 - 1/4 "
Torque	16.8 Nm

No-load speed	750 - 3100 rpm
Rated input power	1900 W
Output power	1240 W
Speed at rated load	2800 rpm
Spindle thread	M 14
Weight (without power cable)	3.8 kg / 8.4 lbs
Cable length	4 m / 13 ft

VIBRATION

Surface grinding	3.38 m/s^2
Uncertainty of measurement K	1.5 m/s^2

NOISE EMISSION

Sound pressure level	95 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

- Bow-type handle
- Milling head pointed
- Flat-pin spanners
- Hexagonal wrench
- Plastic carry case