



Tapered Roller Bearings

Metric Series

Bore Diameter: 15~35mm



■ Dynamic equivalent radial load
 $P_r = X F_r + Y F_a$

$\frac{F_a}{F_r} \leq e$		$\frac{F_a}{F_r} > e$	
X	Y	X	Y
1	0	0.4	Y ₁

Values e and Y₁ from table.

■ Static equivalent radial load
 Larger value of following to be used:
 $P_{0r} = 0.5 F_r + Y_0 F_a$
 $P_{0r} = F_r$
 Values Y₀ from table.

1N=0.102kgf



Boundary dimensions (mm)							Bearing No.	(Ref.) ISO355 Dimension series	Basic dynamic load rating Cr (N)	Basic static load rating Cor (N)	Limiting speed (min ⁻¹)		Abutment and fillet dimensions (mm)								Load center (mm) a (1)	Constant e	Axial load factor		Mass(kg) Reference	Bearing No.
d	D	T	B	C	Cone r (min)	Cup r (min)					Grease lubrication	Oil lubrication	da (min)	db (max)	Da (min)	Db (min)	S1 (min)	S2 (min)	Cone ra (max)	Cup ra (max)			Y1	Y0		
15	35	11.75	11	10	0.6	0.6	H-E30202	—	15800	14500	12000	16000	19.5	20	29	33	2	1.7	0.6	0.6	3.4	0.32	1.88	1.04	0.054	H-E30202
	42	14.25	13	11	1	1	H-E30302J	2FB	21900	19200	10000	14000	20.5	22	36.5	38	2	3	1	1	4.3	0.29	2.11	1.16	0.098	H-E30302J
17	40	13.25	12	11	1	1	H-E30203J	2DB	20800	20700	10000	14000	22.5	23	33	37	2	2	1	1	3.2	0.35	1.74	0.96	0.081	H-E30203J
	47	15.25	14	12	1	1	H-E30303J	2FB	27400	24500	9200	12000	22.5	25	40	42	2	3	1	1	4.3	0.29	2.11	1.16	0.133	H-E30303J
	47	20.25	19	16	1	1	H-32303	—	31900	29900	9400	13000	22.5	25	39	43	2	4	1	1	7.9	0.29	1.97	1.08	0.176	H-32303
20	42	15	15	12	0.6	0.6	H-E32004J	3CC	27300	31500	9300	13000	24.5	25	35	39	3	3	0.6	0.6	4.5	0.37	1.60	0.88	0.102	H-E32004J
	47	15.25	14	12	1	1	H-E30204J	2DB	27000	27200	8700	12000	25.5	27	39	44	2	3	1	1	3.5	0.35	1.74	0.95	0.127	H-E30204J
	47	19.25	18	15	1	1	H-E32204	—	32500	34800	8700	12000	25.5	27	39	43	2	4	1	1	6.2	0.35	1.73	0.95	0.156	H-E32204
	52	16.25	16	13	1.5	1.5	H-E30304J	—	36400	35200	8300	11000	28.5	28	44	47	2	3	1.5	1.5	3.0	0.30	2.00	1.10	0.179	H-E30304J
	52	22.25	21	18	1.5	1.5	H-E32304J	2FD	45100	46700	8400	11000	28.5	27	43	47	3	4	1.5	1.5	7.8	0.30	2.00	1.10	0.239	H-E32304J
25	47	15	15	11.5	0.6	0.6	H-E32005J	4CC	30200	37700	8300	11000	29.5	30	40	44	3	3.5	0.6	0.6	3.2	0.43	1.39	0.77	0.118	H-E32005J
	47	17	17	14	0.6	0.6	H-E33005J	2CE	33500	42300	8300	11000	29.5	30	41	44	3	3	0.6	0.6	6.1	0.29	2.07	1.14	0.131	H-E33005J
	52	16.25	15	13	1	1	H-E30205J	3CC	31500	33700	7500	10000	30.5	31	44	48	2	3	1	1	3.3	0.37	1.60	0.88	0.156	H-E30205J
	52	19.25	18	16	1	1	H-E32205J	2CD	39800	44800	7900	11000	30.5	31	43	48	2	4	1	1	5.7	0.36	1.67	0.92	0.188	H-E32205J
	52	22	22	18	1	1	H-E33205J	2DE	48900	58500	7900	10000	30.5	30	43	49	4	4	1	1	7.9	0.35	1.71	0.94	0.225	H-E33205J
	62	18.25	17	15	1.5	1.5	H-E30305J	2FB	48200	46900	6800	9000	33.5	34	54	57	2	3	1.5	1.5	5.4	0.30	2.00	1.10	0.273	H-E30305J
	62	18.25	17	13	1.5	1.5	H-E30305DJ	7FB	39800	42500	5700	8000	33.5	34	47	58.5	3	5	1.5	1.5	-2.2	0.83	0.73	0.40	0.269	H-E30305DJ
	62	25.25	24	20	1.5	1.5	H-E32305J	2FD	61200	64100	6900	9100	33.5	33	52	57	3	5	1.5	1.5	8.6	0.30	2.00	1.10	0.386	H-E32305J
30	55	17	17	13	1	1	H-E32006J	4CC	38200	48000	7000	9400	35.5	35	47	52	3	4	1	1	3.4	0.43	1.39	0.77	0.177	H-E32006J
	55	20	20	16	1	1	H-E33006J	2CE	43200	55200	7000	9400	35.5	36	48	52	3	4	1	1	7.0	0.29	2.06	1.13	0.203	H-E33006J
	62	17.25	16	14	1	1	H-E30206J	3DB	41500	44800	6500	8700	35.5	37	53	57	2	3	1	1	3.1	0.37	1.60	0.88	0.236	H-E30206J
	62	21.25	20	17	1	1	H-E32206J	3DC	50700	57900	6500	8700	35.5	37	52	58	2	4	1	1	5.3	0.37	1.60	0.88	0.292	H-E32206J
	62	25	25	19.5	1	1	H-E33206J	2DE	66400	79400	6500	8700	35.5	36	53	58	2	5.5	1	1	8.7	0.34	1.76	0.97	0.359	H-E33206J
	72	20.75	19	16	1.5	1.5	H-E30306J	2FB	59600	60100	5800	7700	38.5	40	62	66	3	4.5	1.5	1.5	5.1	0.31	1.90	1.05	0.411	H-E30306J
	72	20.75	19	14	1.5	1.5	H-E30306DJ	7FB	50900	54900	4900	6800	38.5	40	55	68	3	6.5	1.5	1.5	-2.9	0.83	0.73	0.04	0.400	H-E30306DJ
	72	28.75	27	23	1.5	1.5	H-E32306J	2FD	82200	91600	5900	7900	38.5	39	59	66	3	5.5	1.5	1.5	9.8	0.31	1.90	1.05	0.588	H-E32306J
35	55	14	14	11.5	0.6	0.6	E32907J	2BD	26100	36500	6600	8800	39.5	40	49	52	2.5	2.5	0.6	0.6	3.1	0.29	2.06	1.13	0.120	E32907J
	62	18	18	14	1	1	H-E32007J	4CC	45500	59400	6200	8200	40.5	40	54	59	4	4	1	1	2.9	0.45	1.32	0.73	0.231	H-E32007J
	62	21	21	17	1	1	H-E33007J	2CE	51300	68000	6200	8200	40.5	41	55	59	3	4	1	1	6.8	0.31	1.97	1.08	0.263	H-E33007J
	72	18.25	17	15	1.5	1.5	H-E30207J	3DB	55100	60900	5600	7400	43.5	44	62	67	3	3	1.5	1.5	2.9	0.37	1.60	0.88	0.344	H-E30207J
	72	24.25	23	19	1.5	1.5	H-E32207J	3DC	69600	82400	5600	7500	43.5	43	61	67	3	5	1.5	1.5	6.0	0.37	1.60	0.88	0.453	H-E32207J
	72	28	28	22	1.5	1.5	H-E33207J	2DE	86700	107000	5700	7500	43.5	42	61	68	5	6	1.5	1.5	9.6	0.35	1.70	0.93	0.551	H-E33207J
	80	22.75	21	18	2	1.5	H-E30307J	2FB	76200	78900	5200	6900	45	45	70	74	3	4.5	2	1.5	5.8	0.31	1.90	1.05	0.527	H-E30307J
	80	22.75	21	15	2	1.5	H-E30307DJ	7FB	63100	69100	4300	6000	45	44	66	76.5	3	7.5	2	1.5	-4.1	0.83	0.73	0.40	0.536	H-E30307DJ
	80	32.75	31	25	2	1.5	H-E32307J	2FE	101000	114000	5300	7000	45	44	66	74	3	7.5	2	1.5	12.2	0.31	1.90	1.05	0.776	H-E32307J

Note: (1) Minus value of load center "a" indicates that the center is located outside of cone backface.

Tapered Roller Bearings

Metric Series

Bore Diameter: 40~50mm



■ Dynamic equivalent radial load
 $P_r = X F_r + Y F_a$

$\frac{F_a}{F_r} \leq e$		$\frac{F_a}{F_r} > e$	
X	Y	X	Y
1	0	0.4	Y_1

Values e and Y_1 from table.

■ Static equivalent radial load
 Larger value of following to be used:
 $P_{or} = 0.5 F_r + Y_0 F_a$
 $P_{or} = F_r$
 Values Y_0 from table.

1N=0.102kgf



Boundary dimensions (mm)							Bearing No.	(Ref.) ISO355 Dimension series	Basic dynamic load rating Cr (N)	Basic static load rating Cor (N)	Limiting speed (min ⁻¹)		Abutment and fillet dimensions (mm)								Load center (mm) a (1)	Constant e	Axial load factor		Mass(kg) Reference	Bearing No.
d	D	T	B	C	Cone r (min)	Cup r (min)					Grease lubrication	Oil lubrication	da (min)	db (max)	Da (min)	Db (min)	S1 (min)	S2 (min)	Cone ra (max)	Cup ra (max)			Y1	Y0		
40	62	15	15	12	0.6	0.6	H-E32908J	2BC	33500	48500	5900	7800	44.5	45	55	59	3	3	0.6	0.6	3.1	0.29	2.07	1.14	0.164	H-E32908J
	68	19	19	14.5	1	1	H-E32008J	3CD	53500	71400	5600	7400	45.5	46	60	65	4	4.5	1	1	3.9	0.38	1.58	0.87	0.282	H-E32008J
	68	22	22	18	1	1	H-E33008J	2BE	60400	84600	5500	7400	45.5	46	60	65	3	4	1	1	7.3	0.28	2.12	1.17	0.326	H-E33008J
	75	26	26	20.5	1.5	1.5	H-E33108J	2CE	82200	108000	5200	6900	48.5	47	65	71	4	5.5	1.5	1.5	7.7	0.36	1.69	0.93	0.508	H-E33108J
	80	19.75	18	16	1.5	1.5	H-E30208J	3DB	62900	69200	5000	6700	48.5	49	69	75	3	3.5	1.5	1.5	2.7	0.37	1.60	0.88	0.434	H-E30208J
	80	24.75	23	19	1.5	1.5	H-E32208J	3DC	77700	90800	5000	6600	48.5	48	68	75	3	5.5	1.5	1.5	5.3	0.37	1.60	0.88	0.554	H-E32208J
	80	32	32	25	1.5	1.5	H-E33208J	2DE	108000	139000	5000	6700	48.5	47	67	76	5	7	1.5	1.5	11.3	0.36	1.68	0.92	0.758	H-E33208J
	90	25.25	23	20	2	1.5	H-E30308J	2FB	90600	101000	4500	6100	50	52	77	82	3	5	2	1.5	5.4	0.35	1.74	0.96	0.757	H-E30308J
	90	25.25	23	17	2	1.5	H-E30308DJ	7FB	80500	90200	3800	5300	50	51	71	86	3	8	2	1.5	-4.6	0.83	0.73	0.40	0.757	H-E30308DJ
45	90	35.25	33	27	2	1.5	H-E32308J	2FD	116000	139000	4600	6200	50	50	73	82	3	8	2	1.5	10.9	0.35	1.74	0.96	1.06	H-E32308J
	68	15	15	12	0.6	0.6	H-E32909J	2BC	34700	52400	5300	7100	49.5	50	61	64	3	3	0.6	0.6	2.5	0.32	1.88	1.04	0.190	H-E32909J
	75	20	20	15.5	1	1	H-E32009J	3CC	62800	86500	5000	6600	50.5	51	67	72	4	4.5	1	1	3.5	0.39	1.53	0.84	0.354	H-E32009J
	75	24	24	19	1	1	H-E33009J	2CE	69600	101000	5000	6700	50.5	51	67	71	4	5	1	1	7.6	0.29	2.04	1.12	0.416	H-E33009J
	80	26	26	20.5	1.5	1.5	E33109J	3CE	87500	120000	4800	6400	53.5	52	69	76.5	4	5.5	1.5	1.5	6.6	0.38	1.57	0.86	0.563	E33109J
	85	20.75	19	16	1.5	1.5	H-E30209J	3DB	67200	77400	4600	6100	53.5	54	74	80	3	4.5	1.5	1.5	1.8	0.40	1.48	0.81	0.502	H-E30209J
	85	24.75	23	19	1.5	1.5	H-E32209J	3DC	78300	94100	4600	6100	53.5	53	73	81	3	5.5	1.5	1.5	3.8	0.40	1.48	0.81	0.587	H-E32209J
	85	32	32	25	1.5	1.5	E33209J	3DE	112000	149000	4600	6200	53.5	52	76.5	81	5	7	1.5	1.5	10.2	0.39	1.56	0.86	0.803	E33209J
	100	27.25	25	22	2	1.5	E30309J	2FB	113000	128000	4100	5400	55	59	86	93	3	5	2	1.5	5.9	0.35	1.74	0.96	1.01	E30309J
50	100	27.25	25	18	2	1.5	E30309DJ	7FB	95100	107000	3400	4700	55	56	79	96	3	9	2	1.5	-5.7	0.83	0.73	0.40	0.973	E30309DJ
	100	38.25	36	30	2	1.5	E32309J	2FD	146000	180000	4100	5500	55	56	82	93	3	8	2	1.5	11.4	0.35	1.74	0.96	1.43	E32309J
	72	15	15	12	0.6	0.6	E32910J	2BC	35900	56300	4900	6600	54.5	55	65	69	3	3	0.6	0.6	1.3	0.34	1.76	0.97	0.195	E32910J
	80	20	20	15.5	1	1	H-E32010J	3CC	65700	94500	4600	6100	55.5	56	72	77	4	4.5	1	1	2.3	0.42	1.42	0.78	0.389	H-E32010J
	80	24	24	19	1	1	E33010J	2CE	73000	110000	4600	6100	55.5	56	72	76	4	5	1	1	6.6	0.32	1.90	1.04	0.451	E33010J
	85	26	26	20	1.5	1.5	E33110J	3CE	89400	127000	4400	5900	58.5	56	74	81.5	4	6	1.5	1.5	5.4	0.41	1.46	0.80	0.594	E33110J
	90	21.75	20	17	1.5	1.5	H-E30210J	3DB	76500	91700	4300	5700	58.5	58	79	85	3	4.5	1.5	1.5	1.65	0.42	1.43	0.79	0.566	H-E30210J
	90	24.75	23	19	1.5	1.5	H-E32210J	3DC	85000	105000	4300	5700	58.5	58	78	85	3	5.5	1.5	1.5	4.1	0.42	1.43	0.79	0.643	H-E32210J
	90	32	32	24.5	1.5	1.5	H-E33210J	3DE	119000	167000	4300	5700	58.5	57	77	86.5	5	7.5	1.5	1.5	8.9	0.41	1.45	0.80	0.887	H-E33210J
50	110	29.25	27	23	2.5	2	E30310J	2FB	137000	152000	3700	4900	62	65	95	102	3	6	2	2	6.4	0.35	1.74	0.96	1.32	E30310J
	110	29.25	27	19	2.5	2	E30310DJ	7FB	115000	133000	3100	4300	62	62	87	105	3	10	2	2	-5.8	0.83	0.73	0.40	1.25	E30310DJ
	110	42.25	40	33	2.5	2	E32310J	2FD	176000	220000	3700	5000	62	62	90	102	3	9	2	2	12.9	0.35	1.74	0.96	1.89	E32310J

Note: (1) Minus value of load center "a" indicates that the center is located outside of cone backface.

Tapered Roller Bearings

Metric Series

Bore Diameter: 55~65mm



■ Dynamic equivalent radial load
 $P_r = X F_r + Y F_a$

$\frac{F_a}{F_r} \leq e$		$\frac{F_a}{F_r} > e$	
X	Y	X	Y
1	0	0.4	Y ₁

Values e and Y₁ from table.

■ Static equivalent radial load
 Larger value of following to be used:
 $P_{0r} = 0.5 F_r + Y_0 F_a$
 $P_{0r} = F_r$
 Values Y₀ from table.

1N=0.102kgf



Boundary dimensions (mm)							Bearing No.	(Ref.) ISO355 Dimension series	Basic dynamic load rating C _r (N)	Basic static load rating C _{0r} (N)	Limiting speed (min ⁻¹)		Abutment and fillet dimensions (mm)								Load center (mm) a (1)	Constant e	Axial load factor		Mass(kg) Reference	Bearing No.
d	D	T	B	C	Cone r (min)	Cup r (min)					Grease lubrication	Oil lubrication	d _a (min)	d _b (max)	D _a (min)	D _b (min)	S ₁ (min)	S ₂ (min)	Cone r _a (max)	Cup r _a (max)			Y ₁	Y ₀		
55	80	17	17	14	1	1	E32911J	2BC	44600	73300	4400	5900	61	61	72	76	3	3	1	1	2.5	0.31	1.94	1.07	0.285	E32911J
	90	23	23	17.5	1.5	1.5	H-E32011J	3CC	84600	121000	4100	5500	63.5	63	81	86	4	5.5	1.5	1.5	3.2	0.41	1.48	0.81	0.569	H-E32011J
	90	27	27	21	1.5	1.5	E33011J	2CE	96500	149000	4100	5400	63.5	63	81	86	5	6	1.5	1.5	7.3	0.31	1.92	1.06	0.672	E33011J
	95	30	30	23	1.5	1.5	E33111J	3CE	116000	161000	4000	5300	63.5	62	83	91	5	7	1.5	1.5	7.5	0.37	1.60	0.88	0.868	E33111J
	100	22.75	21	18	2	1.5	E30211J	3DB	94600	113000	3900	5200	65	64	88	94	4	4.5	2	1.5	2.0	0.40	1.48	0.81	0.732	E30211J
	100	26.75	25	21	2	1.5	E32211J	3DC	107000	133000	3900	5200	65	63	87	95	4	5.5	2	1.5	3.7	0.40	1.48	0.81	0.863	E32211J
	100	35	35	27	2	1.5	E33211J	3DE	142000	189000	3900	5200	65	62	85	96	6	8	2	1.5	9.7	0.40	1.50	0.83	1.18	E33211J
	120	31.5	29	25	2.5	2	E30311J	2FB	149000	170000	3300	4500	67	71	104	111	4	6.5	2	2	6.0	0.35	1.74	0.96	1.65	E30311J
	120	31.5	29	21	2.5	2	E30311DJ	7FB	129000	148000	2900	4000	67	68	94	113	4	10.5	2	2	-6.9	0.83	0.73	0.40	1.59	E30311DJ
60	120	45.5	43	35	2.5	2	E32311J	2FD	200000	250000	3400	4500	67	68	99	111	4	10.5	2	2	13.1	0.35	1.74	0.96	2.38	E32311J
	85	17	17	14	1	1	E32912J	2BC	46200	78200	4100	5500	65.5	66	77	81	3	3	1	1	1.4	0.33	1.81	1.00	0.306	E32912J
	95	23	23	17.5	1.5	1.5	E32012J	4CC	86100	127000	3900	5200	68.5	67	85	91	4	5.5	1.5	1.5	2.0	0.43	1.39	0.77	0.621	E32012J
	95	27	27	21	1.5	1.5	E33012J	2CE	101000	162000	3900	5200	68.5	67	85	90	5	6	1.5	1.5	6.9	0.33	1.83	1.01	0.719	E33012J
	100	30	30	23	1.5	1.5	E33112J	3CE	118000	170000	3600	4900	68.5	67	88	96	5	7	1.5	1.5	6.3	0.40	1.51	0.83	0.923	E33112J
	110	23.75	22	19	2	1.5	E30212J	3EB	106000	127000	3500	4700	70	70	96	103	4	4.5	2	1.5	1.8	0.40	1.48	0.81	0.945	E30212J
	110	29.75	28	24	2	1.5	E32212J	3EC	132000	167000	3500	4700	70	69	95	104	4	5.5	2	1.5	4.6	0.40	1.48	0.81	1.19	E32212J
	110	38	38	29	2	1.5	E33212J	3EE	174000	239000	3600	4700	70	69	93	105	6	9	2	1.5	10.8	0.40	1.48	0.82	1.57	E33212J
	130	33.5	31	26	3	2.5	E30312J	2FB	173000	201000	3100	4100	74	77	112	120	4	7.5	2.5	2	6.6	0.35	1.74	0.96	2.08	E30312J
65	130	33.5	31	22	3	2.5	E30312DJ	7FB	153000	179000	2600	3700	74	73	103	124	4	11.5	2.5	2	-7.3	0.83	0.73	0.40	2.01	E30312DJ
	130	48.5	46	37	3	2.5	32312J	2FD	221000	275000	3100	4200	74	74	107	120	4	11.5	2.5	2	16.2	0.35	1.74	0.96	2.92	32312J
	90	17	17	14	1	1	E32913J	2BC	47400	83100	3900	5200	70.5	70	81	86	3	3	1	1	0.2	0.35	1.70	0.93	0.327	E32913J
	100	23	23	17.5	1.5	1.5	E32013J	4CC	90000	137000	3600	4800	73.5	72	90	97	4	5.5	1.5	1.5	0.5	0.46	1.31	0.72	0.664	E32013J
	100	27	27	21	1.5	1.5	E33013J	2CE	103000	169000	3600	4800	73.5	72	89	96	5	6	1.5	1.5	5.9	0.35	1.72	0.95	0.762	E33013J
	110	34	34	26.5	1.5	1.5	E33113J	3DE	152000	223000	3400	4600	73.5	73	96	106	6	7.5	1.5	1.5	8.1	0.39	1.55	0.85	1.33	E33113J
	120	24.75	23	20	2	1.5	E30213J	3EB	128000	156000	3200	4300	75	77	106	113	4	4.5	2	1.5	0.6	0.40	1.48	0.81	1.18	E30213J
	120	32.75	31	27	2	1.5	E32213J	3EC	157000	203000	3200	4300	75	76	104	115	4	5.5	2	1.5	6.1	0.40	1.48	0.82	1.58	E32213J
	120	41	41	32	2	1.5	E33213J	3EE	200000	277000	3200	4300	75	74	102	115	7	9	2	1.5	11	0.39	1.54	0.85	2.02	E33213J
65	140	36	33	28	3	2.5	E30313J	2GB	204000	239000	2800	3800	79	83	122	130	4	8	2.5	2	6.7	0.35	1.74	0.96	2.56	E30313J
	140	36	33	23	3	2.5	E30313DJ	7GB	176000	209000	2400	3400	79	79	111	133	4	13	2.5	2	-8.3	0.83	0.73	0.40	2.44	E30313DJ
	140	51	48	39	3	2.5	E32313J	2GD	276000	357000	2900	3900	79	80	117	130	4	12	2.5	2	16.3	0.35	1.74	0.96	3.64	E32313J

Note: (1) Minus value of load center "a" indicates that the center is located outside of cone backface.

Tapered Roller Bearings

Metric Series

Bore Diameter: 70~80mm



■ Dynamic equivalent radial load
 $P_r = X F_r + Y F_a$

$\frac{F_a}{F_r} \leq e$		$\frac{F_a}{F_r} > e$	
X	Y	X	Y
1	0	0.4	Y_1

Values e and Y_1 from table.

■ Static equivalent radial load
 Larger value of following to be used:
 $P_{0r} = 0.5 F_r + Y_0 F_a$
 $P_{0r} = F_r$
 Values Y_0 from table.

1N=0.102kgf



Boundary dimensions (mm)							Bearing No.	(Ref.) ISO355 Dimension series	Basic dynamic load rating Cr (N)	Basic static load rating Cor (N)	Limiting speed (min ⁻¹)		Abutment and fillet dimensions (mm)								Load center (mm) a (1)	Constant e	Axial load factor		Mass(kg) Reference	Bearing No.
d	D	T	B	C	Cone r (min)	Cup r (min)					Grease lubrication	Oil lubrication	da (min)	db (max)	Da (min)	Db (min)	S1 (min)	S2 (min)	Cone ra (max)	Cup ra (max)			Y1	Y0		
70	100	20	20	16	1	1	E32914J	2BC	71000	115000	3500	4700	75.5	77	91	96	4	4	1	1	2.2	0.32	1.90	1.05	0.496	E32914J
	110	25	25	19	1.5	1.5	E32014J	4CC	108000	163000	3300	4400	78.5	78	98	105	5	6	1.5	1.5	1.4	0.43	1.38	0.76	0.884	E32014J
	110	31	31	25.5	1.5	1.5	E33014J	2CE	134000	208000	3300	4400	78.5	78	99	105	5	5.5	1.5	1.5	8.1	0.28	2.11	1.16	1.09	E33014J
	125	26.25	24	21	2	1.5	E30214J	3EB	138000	173000	3100	4100	80	81	110	118	4	5	2	1.5	0.3	0.42	1.43	0.79	1.32	E30214J
	125	33.25	31	27	2	1.5	E32214J	3EC	169000	225000	3100	4100	80	80	108	119	4	6	2	1.5	4.0	0.42	1.43	0.79	1.71	E32214J
	125	41	41	32	2	1.5	E33214J	3EE	206000	294000	3100	4100	80	79	107	120	7	9	2	1.5	9.8	0.41	1.47	0.81	2.16	E33214J
	150	38	35	30	3	2.5	E30314J	2GB	230000	273000	2600	3500	84	89	130	140	4	8	2.5	2	7.5	0.35	1.74	0.96	3.08	E30314J
	150	38	35	25	3	2.5	E30314DJ	7GB	197000	235000	2300	3200	84	84	118	142	4	13	2.5	2	-9.1	0.83	0.73	0.40	2.97	E30314DJ
75	105	20	20	16	1	1	E32915J	2BC	73600	123000	3300	4400	80.5	81	97	101	4	4	1	1	1.1	0.33	1.80	0.99	0.526	E32915J
	115	25	25	19	1.5	1.5	E32015J	4CC	110000	169000	3100	4200	83.5	83	103	110	5	6	1.5	1.5	-0.1	0.46	1.31	0.72	0.93	E32015J
	115	31	31	25.5	1.5	1.5	E33015J	2CE	141000	225000	3000	4100	83.5	83	104	110	6	5.5	1.5	1.5	8.1	0.30	2.01	1.11	1.16	E33015J
	125	37	37	29	2	1.5	E33115J	3DE	186000	280000	3000	4000	85	84	109	120	6	8	2	1.5	7.5	0.40	1.51	0.83	1.84	E33115J
	130	27.25	25	22	2	1.5	E30215J	4DB	142000	181000	2900	3900	85	86	115	124	4	5	2	1.5	-0.3	0.44	1.38	0.76	1.42	E30215J
	130	33.25	31	27	2	1.5	E32215J	4DC	174000	234000	2900	3900	85	85	114	123	4	6	2	1.5	3.0	0.44	1.38	0.76	1.77	E32215J
	130	41	41	31	2	1.5	E33215J	3EE	212000	310000	2900	3900	85	83	111	125	7	10	2	1.5	8.5	0.43	1.40	0.77	2.26	E33215J
	160	40	37	31	3	2.5	E30315	2GB	250000	297000	2500	3300	89	95	139	149	4	9	2.5	2	8.1	0.35	1.73	0.95	3.52	E30315
80	110	20	20	16	1	1	E32916J	2BC	76100	131000	3100	4200	85.5	86	101	106	4	4	1	1	-0.1	0.35	1.71	0.94	0.556	E32916J
	125	29	29	22	1.5	1.5	E32016J	3CC	147000	225000	2900	3900	88.5	89	112	120	6	7	1.5	1.5	2.3	0.42	1.42	0.78	1.32	E32016J
	125	36	36	29.5	1.5	1.5	E33016J	2CE	173000	288000	2900	3900	88.5	90	112	119	6	6.5	1.5	1.5	10.9	0.28	2.16	1.19	1.63	E33016J
	130	37	37	29	2	1.5	E33116J	3DE	191000	294000	2800	3800	90	89	114	126	6	8	2	1.5	6.5	0.42	1.44	0.79	1.93	E33116J
	140	28.25	26	22	2.5	2	E30216J	3EB	161000	202000	2700	3600	92	91	124	132	4	6	2	2	-0.3	0.42	1.43	0.79	1.72	E30216J
	140	35.25	33	28	2.5	2	E32216J	3EC	203000	271000	2700	3600	92	90	122	134	4	7	2	2	3.8	0.42	1.43	0.79	2.17	E32216J
	140	46	46	35	2.5	2	E33216	3EE	250000	371000	2700	3600	92	89	119	135	7	11	2	2	10.3	0.43	1.41	0.78	2.99	E33216
	170	42.5	39	33	3	2.5	E30316J	2GB	294000	355000	2300	3100	94	102	148	159	4	9.5	2.5	2	7.7	0.35	1.73	0.96	4.46	E30316J
80	170	42.5	39	27	3	2.5	E30316DJ	7GB	236000	282000	2000	2800	94	97	134	159	6	15.5	2.5	2	-11.0	0.83	0.73	0.40	4.12	E30316DJ
	170	61.5	58	48	3	2.5	E32316	2GD	378000	497000	2300	3100	94	98	142	159	4	13.5	2.5	2	19.5	0.35	1.73	0.95	6.32	E32316

Note: (1) Minus value of load center "a" indicates that the center is located outside of cone backface.

Tapered Roller Bearings

Metric Series

Bore Diameter: 85~95mm



Dynamic equivalent radial load

$$Pr = XFr + YFa$$

$\frac{Fa}{Fr} \leq e$		$\frac{Fa}{Fr} > e$	
X	Y	X	Y
1	0	0.4	Y ₁

Values e and Y₁ from table.

Static equivalent radial load

Larger value of following to be used:

$$P_0 = 0.5Fr + Y_0Fa$$

$$P_0 = Fr$$

Values Y₀ from table.

1N=0.102kgf

Boundary dimensions (mm)							Bearing No.	(Ref.) ISO355 Dimension series	Basic dynamic load rating Cr (N)	Basic static load rating Cor (N)	Limiting speed (min ⁻¹)		Abutment and fillet dimensions (mm)										Load center (mm) a (1)	Constant e	Axial load factor		Mass(kg) Reference	Bearing No.
d	D	T	B	C	Cone r (min)	Cup r (min)					Grease lubrication	Oil lubrication	d _a (min)	d _b (max)	D _a (min)	D _b (min)	S ₁ (min)	S ₂ (min)	Cone ra (max)	Cup ra (max)	Y ₁	Y ₀						
85	120	23	23	18	1.5	1.5	E32917J	2BC	97100	165000	2900	3900	93.5	93	109	115	5	5	1.5	1.5	1.8	0.33	1.83	1.01	0.794	E32917J		
	130	29	29	22	1.5	1.5	E32017J	4CC	150000	234000	2800	3700	93.5	94	117	125	6	7	1.5	1.5	1.0	0.44	1.36	0.75	1.38	E32017J		
	130	36	36	29.5	1.5	1.5	E33017J	2CE	177000	300000	2800	3700	93.5	94	118	125	6	6.5	1.5	1.5	9.7	0.29	2.06	1.13	1.72	E33017J		
	140	41	41	32	2.5	2.5	E33117J	3DE	224000	346000	2600	3500	97	95	122	135	7	9	2	2	7.8	0.41	1.48	0.81	2.43	E33117J		
	150	30.5	28	24	2.5	2	E30217J	3EB	182000	231000	2500	3400	97	97	132	141	5	6.5	2	2	0.1	0.42	1.43	0.79	2.17	E30217J		
	150	38.5	36	30	2.5	2	E32217J	3EC	232000	315000	2500	3300	97	96	130	142	5	8.5	2	2	4.3	0.42	1.43	0.79	2.80	E32217J		
	150	49	49	37	2.5	2	E33217J	3EE	294000	439000	2500	3400	97	95	128	144	7	12	2	2	11.9	0.42	1.43	0.79	3.63	E33217J		
	180	44.5	41	34	4	3	E30317	—	305000	367000	2200	2900	103	107	156	167	5	10.5	3	2.5	8.7	0.35	1.73	0.95	4.97	E30317		
90	180	44.5	41	28	4	3	E30317DJ	—	263000	317000	1900	2600	103	103	143	169	6	16.5	3	2.5	-11.8	0.83	0.73	0.41	4.81	E30317DJ		
	180	63.5	60	49	4	3	E32317J	2GD	439000	587000	2200	3000	103	103	150	167	5	14.5	3	2.5	19.7	0.35	1.74	0.96	7.42	E32317J		
	125	23	23	18	1.5	1.5	E32918J	2BC	101000	175000	2800	3700	98.5	97	114	120	5	5	1.5	1.5	0.7	0.34	1.75	0.96	0.834	E32918J		
	140	32	32	24	2	1.5	E32018J	3CC	178000	276000	2600	3500	100	100	125	134	6	8	2	1.5	2.2	0.42	1.42	0.78	1.80	E32018J		
	140	39	39	32.5	2	2	E33018J	2CE	221000	367000	2600	3400	100	100	127	135	7	6.5	2	1.5	11.9	0.27	2.23	1.23	2.22	E33018J		
	160	32.5	30	26	2.5	2	E30218J	3FB	204000	261000	2400	3200	102	103	140	150	5	6.5	2	2	-0.1	0.42	1.43	0.79	2.65	E30218J		
	160	42.5	40	34	2.5	2	E32218J	3FC	263000	362000	2400	3200	102	102	138	152	5	8.5	2	2	5.5	0.42	1.43	0.79	3.47	E32218J		
	190	46.5	43	36	4	3	E30318	—	336000	407000	2100	2700	108	113	165	177	5	10.5	3	2.5	9.3	0.35	1.73	0.95	5.78	E30318		
95	190	46.5	43	30	4	3	E30318D	—	282000	336000	1700	2400	108	109	151	179	6	16.5	3	2.5	-12.6	0.81	0.74	0.41	5.60	E30318D		
	190	67.5	64	53	4	3	E32318J	—	461000	614000	2100	2800	108	108	157	177	5	14.5	3	2.5	20.9	0.35	1.74	0.96	8.61	E32318J		
	130	23	23	18	1.5	1.5	E32919J	2BC	104000	186000	2600	3500	103.5	102	119	125	5	5	1.5	1.5	-0.5	0.36	1.68	0.92	0.876	E32919J		
	145	32	32	24	2	1.5	E32019J	4CC	182000	287000	2500	3300	105	105	130	140	6	8	2	1.5	0.8	0.44	1.36	0.75	1.88	E32019J		
	145	39	39	32.5	2	1.5	E33019J	2CE	226000	382000	2500	3300	105	104	131	139	7	6.5	2	1.5	11.2	0.28	2.16	1.19	2.31	E33019J		
	170	34.5	32	27	3	2.5	E30219J	3FB	231000	299000	2200	3000	109	110	149	159	5	7.5	2.5	2	-0.4	0.42	1.43	0.79	3.20	E30219J		
	170	45.5	43	37	3	2.5	E32219J	3FC	311000	439000	2200	3000	109	108	145	161	5	8.5	2.5	2	6.6	0.42	1.43	0.79	4.34	E32219J		
	170	58	58	44	3	2.5	E33219J	3FE	374000	582000	2200	2900	109	107	144	163	9	14	2.5	2	15.2	0.41	1.47	0.81	5.66	E33219J		
95	200	49.5	45	38	4	3	30319	—	317000	368000	2000	2600	113	118	172	186	5	11.5	3	2.5	9.7	0.35	1.73	0.95	6.32	30319		
	200	49.5	45	32	4	3	E30319DJ	—	319000	391000	1700	2300	113	113	157	187	6	17.5	3	2.5	-13.2	0.81	0.73	0.40	6.68	E30319DJ		
	200	71.5	67	55	4	3	E32319J	—	517000	695000	2000	2600	113	115	166	186	5	16.5	3	2.5	21.7	0.35	1.74	0.96	10.1	E32319J		

Note: (1) Minus value of load center "a" indicates that the center is located outside of cone backface.