

Poliflex fine grinding points PF ZY LR


A hard, sturdy bond with white aluminium oxide. Suitable for use on surfaces. Grinding point in cylindrical shape, for fine grinding of small surfaces.



Special features:

- Produces a fine, shiny surface finish.
- High economic efficiency due to high abrasive performance and long tool life.

D [mm]	T [mm]	S _d [mm]	L ₂ [mm]	Abrasive	Grit size	Opt. RPM	Max. RPM		Item no.	Designation
4	8	3	30	A	120	95,000	143,200	10	41200212	PF ZY 0408/3 AW 120 LR
					400	95,000	143,200	10	41200240	PF ZY 0408/3 AW 400 LR
6	10	3	30	A	120	64,000	95,400	10	41200612	PF ZY 0610/3 AW 120 LR
8	8	3	30	A	120	47,500	71,600	10	41201212	PF ZY 0808/3 AW 120 LR
					120	47,500	71,600	10	41204212	PF ZY 0812/3 AW 120 LR
					220	47,500	71,600	10	41204220	PF ZY 0812/3 AW 220 LR
					400	47,500	71,600	10	41204240	PF ZY 0812/3 AW 400 LR
10	10	3	30	A	120	38,000	57,200	10	41207212	PF ZY 1010/3 AW 120 LR
					220	38,000	57,200	10	41207220	PF ZY 1010/3 AW 220 LR
	15	3	30	A	120	38,000	57,200	10	41213212	PF ZY 1015/3 AW 120 LR
12	12	3	30	A	120	32,000	47,700	10	41222212	PF ZY 1212/3 AW 120 LR
	20	3	30	A	120	32,000	47,700	10	41228212	PF ZY 1220/3 AW 120 LR
10	10	6	40	A	120	38,000	57,200	10	41210212	PF ZY 1010/6 AW 120 LR
					120	38,000	57,200	10	41216212	PF ZY 1015/6 AW 120 LR
					120	38,000	57,200	10	41219212	PF ZY 1025/6 AW 120 LR
					220	38,000	57,200	10	41219220	PF ZY 1025/6 AW 220 LR
12	12	6	40	A	120	32,000	47,700	10	41225212	PF ZY 1212/6 AW 120 LR
	20	6	40	A	120	32,000	47,700	10	41231212	PF ZY 1220/6 AW 120 LR
15	15	6	40	A	120	25,500	38,100	10	41234212	PF ZY 1515/6 AW 120 LR
	25	6	40	A	120	25,500	38,100	10	41237212	PF ZY 1525/6 AW 120 LR
	30	6	40	A	120	25,500	38,100	10	41240212	PF ZY 1530/6 AW 120 LR
20	20	6	40	A	120	19,000	28,600	10	41243212	PF ZY 2020/6 AW 120 LR
	30	6	40	A	120	19,000	28,600	10	41246212	PF ZY 2030/6 AW 120 LR
25	25	6	40	A	120	15,000	22,900	10	41249212	PF ZY 2525/6 AW 120 LR
30	30	6	40	A	120	12,500	19,000	5	41252212	PF ZY 3030/6 AW 120 LR



Poliflex fine grinding points PF KU LR

A hard, sturdy bond with white aluminium oxide. Suitable for use on surfaces. Grinding point in ball shape for fine grinding inner radii, contours and transitions.




Special features:

- Produces a fine, shiny surface finish.
- High economic efficiency due to high abrasive performance and long tool life.

D [mm]	S _d [mm]	L ₂ [mm]	Abrasive	Grit size	Opt. RPM	Max. RPM		Item no.	Designation
8	3	30	A	120	47,000	71,600	10	41401212	PF KU 08/3 AW 120 LR
10	3	30	A	120	38,000	57,200	10	41410212	PF KU 10/3 AW 120 LR
15	6	40	A	120	29,500	38,100	10	41434212	PF KU 15/6 AW 120 LR
20	6	40	A	120	19,000	28,600	10	41443212	PF KU 20/6 AW 120 LR

LHR bond



Poliflex fine grinding points PF ZY LHR

A hard, sturdy bond. Suitable for use on edges. Grinding point in cylindrical shape, for fine grinding of small surfaces.

Special features:

- Produces a fine, shiny surface finish.
- High economic efficiency due to high abrasive performance and long tool life.

D [mm]	T [mm]	S _d [mm]	L ₂ [mm]	Abrasive	Grit size	Opt. RPM	Max. RPM		Item no.	Designation
8	12	3	30	A	120	47,000	76,700	10	41204312	PF ZY 0812/3 AW 120 LHR
10	25	6	40	A/SiC	60	75,000	83,200	10	41219306	PF ZY 1025/6 AWCN 60 LHR
				A	120	75,000	83,200	10	41219312	PF ZY 1025/6 AW 120 LHR
20	20	6	40	A	120	38,000	47,700	10	41243312	PF ZY 2020/6 AW 120 LHR

