

Aluminium oxide A version


For general grinding work from coarse to fine grinding in industry and professional trades.



Special features:

- High economic efficiency thanks to long tool life and very high stock removal rate.
- Consistent surface finish thanks to high-quality abrasives. Highly flexible, enabling optimal adjustment to the contour.
- Optimal adjustment to the contour in conjunction with the matching backing pad. Please order backing pad separately.

D [mm]	H [mm]	Abrasive	Grit size	Max. RPM		Item no.	Designation
slotted							
115	22	A	16	13,300	25	64101111	FS 115-22 A 16
			24	13,300	25	64102111	FS 115-22 A 24
			36	13,300	25	64103111	FS 115-22 A 36
			50	13,300	25	64105111	FS 115-22 A 50
			60	13,300	25	64106111	FS 115-22 A 60
			80	13,300	25	64108111	FS 115-22 A 80
			100	13,300	25	64110111	FS 115-22 A 100
			120	13,300	25	64112111	FS 115-22 A 120
125	22	A	16	12,200	25	64101125	FS 125-22 A 16
			24	12,200	25	64102125	FS 125-22 A 24
			36	12,200	25	64103125	FS 125-22 A 36
			50	12,200	25	64105125	FS 125-22 A 50
			60	12,200	25	64106125	FS 125-22 A 60
			80	12,200	25	64108125	FS 125-22 A 80
			100	12,200	25	64110125	FS 125-22 A 100
			120	12,200	25	64112125	FS 125-22 A 120
150	22	A	36	10,200	25	64103155	FS 150-22 A 36
			60	10,200	25	64106155	FS 150-22 A 60
			80	10,200	25	64108155	FS 150-22 A 80
180	22	A	16	8,500	25	64101175	FS 180-22 A 16
			24	8,500	25	64102175	FS 180-22 A 24
			36	8,500	25	64103175	FS 180-22 A 36
			50	8,500	25	64105175	FS 180-22 A 50
			60	8,500	25	64106175	FS 180-22 A 60
			80	8,500	25	64108175	FS 180-22 A 80
			100	8,500	25	64110175	FS 180-22 A 100
			120	8,500	25	64112175	FS 180-22 A 120
unslotted							
100	16	A	16	15,300	25	69401127	FS 100-16 A 16
			24	15,300	25	69401016	FS 100-16 A 24
			36	15,300	25	69401015	FS 100-16 A 36
			50	15,300	25	69401065	FS 100-16 A 50
			60	15,300	25	69401023	FS 100-16 A 60
			80	15,300	25	69401024	FS 100-16 A 80
			100	15,300	25	69401019	FS 100-16 A 100
			120	15,300	25	69401067	FS 100-16 A 120



Zirconia alumina Z version

For coarse grinding work with a high stock removal rate and a long tool life.

Special features:

- High economic efficiency thanks to long tool life and very high stock removal rate.
- Consistent surface finish thanks to high-quality abrasives. Highly flexible, enabling optimal adjustment to the contour.
- Optimal adjustment to the contour in conjunction with the matching backing pad. Please order backing pad separately.

D [mm]	H [mm]	Abrasive	Grit size	Max. RPM		Item no.	Designation
-----------	-----------	----------	-----------	----------	---	----------	-------------

slotted

115	22	Z	24	13,300	25	64202111	FS 115-22 Z 24
			36	13,300	25	64203111	FS 115-22 Z 36
			50	13,300	25	64205111	FS 115-22 Z 50
			60	13,300	25	64206111	FS 115-22 Z 60
			80	13,300	25	64208111	FS 115-22 Z 80
			120	13,300	25	64212111	FS 115-22 Z 120
125	22	Z	24	12,200	25	64202125	FS 125-22 Z 24
			36	12,200	25	64203125	FS 125-22 Z 36
			50	12,200	25	64205125	FS 125-22 Z 50
			60	12,200	25	64206125	FS 125-22 Z 60
			80	12,200	25	64208125	FS 125-22 Z 80
			120	12,200	25	64212125	FS 125-22 Z 120
180	22	Z	24	8,500	25	64202175	FS 180-22 Z 24
			36	8,500	25	64203175	FS 180-22 Z 36
			50	8,500	25	64205175	FS 180-22 Z 50
			60	8,500	25	64206175	FS 180-22 Z 60
			80	8,500	25	64208175	FS 180-22 Z 80
			120	8,500	25	64212175	FS 180-22 Z 120

unslotted

100	16	Z	24	15,300	25	69401548	FS 100-16 Z 24
			36	15,300	25	69401549	FS 100-16 Z 36
			50	15,300	25	69401550	FS 100-16 Z 50
			60	15,300	25	69401495	FS 100-16 Z 60
			80	15,300	25	69401551	FS 100-16 Z 80
			100	15,300	25	69401496	FS 100-16 Z 100
			120	15,300	25	69401552	FS 100-16 Z 120