
Diamond tools for the construction industry

Segmented diamond cut-off wheels for fast cutting





DS START type


General-purpose segmented-rim tool for aggressive, fast cutting with high cutting performance and a good tool life.

Special features:

- High diamond qualities.
- Good cutting characteristics and short cutting times.
- Good ease of cutting and high economic efficiency.

D [mm]	T [mm]	H [mm]	H_R [mm]	X [mm]	Max. RPM		Item no.	Designation
100	1.6	20	16	7	15,300	1	68300037	DS 100x1.6x16/20 START
110	1.6	20	-	7	13,800	1	68300052	DS 110X1.6X20 START
115	1.6	22.23	-	7	13,300	1	68300044	DS 115x1.6x22.23 START
125	1.6	22.23	-	7	12,200	1	68300045	DS 125x1.6x22.23 START
178	2	22.23	-	7	8,600	1	68300038	DS 178x2.0x22.23 START
230	2.3	22.23	-	7	6,600	1	68300039	DS 230x2.3x22.23 START
300	2.8	25.4	20	8	6,400	1	68300053	DS 300X2.8X20/25.4 START
350	3.2	25.4	-	8	5,400	1	68300047	DS 350x3.2x25.4 START
400	3.2	25.4	-	10	4,800	1	68300054	DS 400X3.2X25.4 START
450	3.2	25.4	-	10	4,200	1	68300055	DS 450X3.2X25.4 START





DS PSF type

General-purpose segmented-edge tool for aggressive, fast cutting with high cutting performance and an ideal tool life. With laser-welded segments.

Special features:

- High diamond qualities.
- Excellent cutting characteristics and short cutting times.
- High ease of cutting and economic efficiency.

D [mm]	T [mm]	H [mm]	X [mm]	Max. RPM		Item no.	Designation
115	2.2	22.23	10	13,300	1	68011221	DS 115 x 2,2 x 22,23 PSF
125	2.2	22.23	10	12,200	1	68012221	DS 125 x 2,2 x 22,23 PSF
150	2.2	22.23	10	10,200	1	68300102	DS 150x2.2x22.23 PSF
178	2.4	22.23	10	8,600	1	68017221	DS 178 x 2,4 x 22,23 PSF
230	2.4	22.23	10	6,600	1	68023223	DS 230 x 2,4 x 22,23 PSF

New item