



PSF STEEL ★★☆☆

Cut-off wheel for steel with high cutting performance and good tool life. Suitable for cutting sheet metal, profiles and solid material, and for cutting out holes.



Special features:

- Fast work progress thanks to good cutting performance.
- High economic efficiency due to good tool life.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.


D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-------------	-----------	----------	----------	---	----------	-------------

Flat design EHT (shape 41)



100	2.4	16	15,300	A	25	61741116	EHT 100-2,4 PSF STEEL/16,0
105	1	16	14,500	A	25	69121029	EHT 105-1,0 PSF STEEL/16,0
115	1	22.23	13,300	A	25	61730010	EHT 115-1,0 PSF STEEL
	1.6	22.23	13,300	A	25	61730021	EHT 115-1,6 PSF STEEL
	2.4	22.23	13,300	A	25	61730026	EHT 115-2,4 PSF STEEL
125	1	22.23	12,200	A	25	61719010	EHT 125-1,0 PSF STEEL
	1.6	22.23	12,200	A	25	61719021	EHT 125-1,6 PSF STEEL
	2.4	22.23	12,200	A	25	61719026	EHT 125-2,4 PSF STEEL
150	1.6	22.23	10,200	A	25	61721221	EHT 150-1,6 PSF STEEL
180	1.6	22.23	8,500	A	25	61719121	EHT 180-1,6 PSF STEEL
	3	22.23	8,500	A	25	61726222	EHT 180-3,0 PSF STEEL
230	1.9	22.23	6,600	A	25	61728231	EHT 230-1,9 PSF STEEL
	3	22.23	6,600	A	25	61728222	EHT 230-3,0 PSF STEEL

Depressed-centre design EH (shape 42)



100	2.4	16	15,300	A	25	61739116	EH 100-2,4 PSF STEEL/16,0
115	2.4	22.23	13,300	A	25	61740122	EH 115-2,4 PSF STEEL
	3.2	22.23	13,300	A	25	61740126	EH 115-3,2 PSF STEEL
125	2.4	22.23	12,200	A	25	61720222	EH 125-2,4 PSF STEEL
	3.2	22.23	12,200	A	25	61720226	EH 125-3,2 PSF STEEL
180	3	22.23	8,500	A	25	61723222	EH 180-3,0 PSF STEEL
230	3	22.23	6,600	A	25	61724222	EH 230-3,0 PSF STEEL





PSF STEELOX ★★☆☆

Cut-off wheel for steel and stainless steel (INOX) with high cutting performance and good tool life. Suitable for cutting sheet metal, profiles and solid material, and for cutting out holes.




Special features:

- Fast work progress due to high cutting performance and high efficiency thanks to excellent tool life.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.
- Thin cut-off wheels are ideal for cordless angle grinders.

D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-------------	-----------	----------	----------	---	----------	-------------

Flat design EHT (shape 41)



115	1	22.23	13,300	A	10	69121092	EHT 115-1,0 PSF STEELOX (TIN 10)
125	1	22.23	12,200	A	10	69121091	EHT 125-1,0 PSF STEELOX (TIN 10)
76	0.8	10	20,100	A	25	65508109	EHT 76-0,8 PSF STEELOX/10,0
	1	10	20,100	A	25	65508100	EHT 76-1,0 PSF STEELOX/10,0
105	1	16	14,500	A	25	61741105	EHT 105-1,0 PSF STEELOX/16,0
115	1	22.23	13,300	A	25	61730100	EHT 115-1,0 PSF STEELOX
	1.6	22.23	13,300	A	25	61730121	EHT 115-1,6 PSF STEELOX
	2.4	22.23	13,300	A	25	61730122	EHT 115-2,4 PSF STEELOX
125	1	22.23	12,200	A	25	61721100	EHT 125-1,0 PSF STEELOX
					10	61721110	EHT 125-1,0 PSF STEELOX (10)
	1.6	22.23	12,200	A	25	61721121	EHT 125-1,6 PSF STEELOX
	2	22.23	12,200	A	25	69120850	EHT 125-2,0 PSF STEELOX
	2.4	22.23	12,200	A	25	61721122	EHT 125-2,4 PSF STEELOX
150	1.6	22.23	10,200	A	25	61724121	EHT 150-1,6 PSF STEELOX
180	1.6	22.23	8,500	A	25	61726121	EHT 180-1,6 PSF STEELOX
	2.5	22.23	8,500	A	25	61726122	EHT 180-2,5 PSF STEELOX
230	1.9	22.23	6,600	A	25	61728131	EHT 230-1,9 PSF STEELOX
	2	22.23	6,600	A	25	69901410	EHT 230-2,0 PSF STEELOX
	2.5	22.23	6,600	A	25	61728122	EHT 230-2,5 PSF STEELOX

Flat reinforced type EHT (shape 41) – prevents wobbling in separating cuts.



230	1.9	22.23	6,600	A	25	61728327	EHT 230-1,9 PSF HD STEELOX
-----	-----	-------	-------	---	----	----------	----------------------------


Flat design EHT (type 41) with X-LOCK holder



X-LOCK

115	1	22.23	13,300	A	25	61730101	EHT 115-1,0 PSF STEELOX/X-LOCK
	1.6	22.23	13,300	A	25	61730124	EHT 115-1,6 PSF STEELOX/X-LOCK
125	1	22.23	12,200	A	25	61721101	EHT 125-1,0 PSF STEELOX/X-LOCK
	1.6	22.23	12,200	A	25	61721124	EHT 125-1,6 PSF STEELOX/X-LOCK

Depressed-centre design EH (shape 42)



100	2.4	16	15,300	A	25	61739326	EH 100-2,4 PSF STEELOX/16,0
115	2.4	22.23	13,300	A	25	61740326	EH 115-2,4 PSF STEELOX
125	2.4	22.23	12,200	A	25	61720326	EH 125-2,4 PSF STEELOX
180	2.5	22.23	8,500	A	25	61726326	EH 180-2,5 PSF STEELOX
230	2.5	22.23	6,600	A	25	61728326	EH 230-2,5 PSF STEELOX

Depressed-centre design EH (type 42) with X-LOCK holder



X-LOCK

125	2.4	22.23	12,200	A	25	61740125	EH 125-2,4 PSF STEELOX/X-LOCK
-----	-----	-------	--------	---	----	----------	-------------------------------



PSF CLASSIC STEELOX ★★☆☆

Cut-off wheel for steel and stainless steel (INOX) with high cutting performance, good tool life and metal ring in the inner hole. Suitable for cutting sheet metal, profiles and solid material, and for cutting out holes.



Special features:

- Fast work progress due to high cutting performance and high efficiency thanks to excellent tool life.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.
- Suitable for general use on steel and stainless steel (INOX).

D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
Flat design EHT (shape 41) 							
115	1	22.23	13,300	A	25	61715150	EHT 115-1,0 PSF CLASSIC STEELOX
125	1	22.23	12,200	A	25	61715250	EHT 125-1,0 PSF CLASSIC STEELOX
	1.6	22.23	12,200	A	25	61715253	EHT 125-1,6 PSF CLASSIC STEELOX



PSF DUODISC STEELOX ★★☆☆ combination wheel

Combination wheel for steel and stainless steel (INOX) with high cutting performance and good tool life. Suitable for cutting, deburring, grouting, surface grinding, and for work on fillet welds and weld seams.



Special features:

- Safe, standard-compliant solution for cutting and face grinding with just one tool.
- Ideal for cordless angle grinders.
- Problem solver for grinding work on scale.

D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
Depressed-centre design E (type 27) 							
100	1.9	16	15,300	A	10	62010630	E 100-1,9 PSF DUO STEELOX/16,0
	2.8	16	15,300	A	10	62010632	E 100-2,8 PSF DUO STEELOX/16,0
115	1.9	22.23	13,300	A	10	62011630	E 115-1,9 PSF DUO STEELOX
	2.8	22.23	13,300	A	10	62011620	E 115-2,8 PSF DUO STEELOX
125	1.9	22.23	12,200	A	10	62012630	E 125-1,9 PSF DUO STEELOX
	2.8	22.23	12,200	A	10	62012620	E 125-2,8 PSF DUO STEELOX
150	3.5	22.23	10,200	A	10	62015420	E 150-3,5 PSF DUO STEELOX
180	3.5	22.23	8,500	A	10	62017420	E 180-3,5 PSF DUO STEELOX





PSF ALU + STONE ★★☆☆

Cut-off wheel with high cutting performance and good tool life for use on aluminium, titanium, other non-ferrous metals, stone, concrete, tiles, duroplastics, cast iron. Suitable for cutting sheet metal, profiles and solid material, and for cutting out holes.



Special features:

- Fast work progress thanks to good cutting performance.
- Thin cut-off wheels are ideal for cordless angle grinders.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.

D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-------------	-----------	----------	----------	---	----------	-------------

Flat design EHT (shape 41)



115	1	22.23	13,300	C	25	61818010	EHT 115-1,0 PSF ALU+STONE
	1.6	22.23	13,300	C	25	61818021	EHT 115-1,6 PSF ALU+STONE
125	1	22.23	12,200	C	25	61819010	EHT 125-1,0 PSF ALU+STONE
					10	61819015	EHT 125-1,0 PSF ALU+STONE (10)
	1.6	22.23	12,200	C	25	61819021	EHT 125-1,6 PSF ALU+STONE
180	3.2	22.23	8,500	C	25	61826222	EHT 180-3,2 PSF ALU+STONE
230	3.2	22.23	6,600	C	25	61828222	EHT 230-3,2 PSF ALU+STONE

Depressed-centre design EH (shape 42)



115	2.4	22.23	13,300	C	25	61830122	EH 115-2,4 PSF ALU+STONE
125	2.4	22.23	12,200	C	25	61820222	EH 125-2,4 PSF ALU+STONE
150	3	22.23	10,200	C	25	61823326	EH 150-3,0 PSF ALU+STONE
180	3.2	22.23	8,500	C	25	61823222	EH 180-3,2 PSF ALU+STONE
230	3.2	22.23	6,600	C	25	61824222	EH 230-3,2 PSF ALU+STONE





SG STEEL ★★☆☆

Cut-off wheel for steel with high cutting performance and maximum tool life. Suitable for cutting profiles and solid material, and for cutting out holes.



Special features:

- Fast work progress thanks to good cutting performance.
- Thin cut-off wheels are ideal for cordless angle grinders.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.


D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-------------	-----------	----------	----------	---	----------	-------------

Flat design EHT (shape 41)



100	2.4	16	15,300	A	25	61340116	EHT 100-2,4 SG STEEL/16,0
115	1	22.23	13,300	A	25	61340382	EHT 115-1,0 SG STEEL
	1.6	22.23	13,300	A	25	61330122	EHT 115-1,6 SG STEEL
	2.4	22.23	13,300	A	25	61340222	EHT 115-2,4 SG STEEL
125	1	22.23	12,200	A	25	61341082	EHT 125-1,0 SG STEEL
	1.6	22.23	12,200	A	25	61331122	EHT 125-1,6 SG STEEL
	2.4	22.23	12,200	A	25	61321222	EHT 125-2,4 SG STEEL
150	1.6	22.23	10,200	A	25	61323106	EHT 150-1,6 SG STEEL
	3	22.23	10,200	A	25	61322222	EHT 150-3,0 SG STEEL
180	1.6	22.23	8,500	A	25	61326122	EHT 180-1,6 SG STEEL
	2.9	22.23	8,500	A	25	61326322	EHT 180-2,9 SG STEEL
	3.2	22.23	8,500	A	25	61326222	EHT 180-3,2 SG STEEL
230	1.9	22.23	6,600	A	25	61328131	EHT 230-1,9 SG STEEL
	2.9	22.23	6,600	A	25	61328322	EHT 230-2,9 SG STEEL
	3.2	22.23	6,600	A	25	61328222	EHT 230-3,2 SG STEEL

Depressed-centre design EH (shape 42)



100	2.4	16	15,300	A	25	61339116	EH 100-2,4 SG STEEL/16,0
115	2.4	22.23	13,300	A	25	61340122	EH 115-2,4 SG STEEL
	3.2	22.23	13,300	A	25	61340132	EH 115-3,2 SG STEEL
125	2.4	22.23	12,200	A	25	61320222	EH 125-2,4 SG STEEL
	3.2	22.23	12,200	A	25	61320232	EH 125-3,2 SG STEEL
150	3	22.23	10,200	A	25	61323122	EH 150-3,0 SG STEEL
180	2.9	22.23	8,500	A	25	61323322	EH 180-2,9 SG STEEL
	3.2	22.23	8,500	A	25	61323222	EH 180-3,2 SG STEEL
230	2.9	22.23	6,600	A	25	61324322	EH 230-2,9 SG STEEL
	3.2	22.23	6,600	A	25	61324222	EH 230-3,2 SG STEEL





SG STEELOX ★★☆☆

Cut-off wheel for steel and stainless steel (INOX) with high cutting performance and maximum tool life. Suitable for cutting sheet metal, profiles and solid material, and for cutting out holes.



Special features:

- Fast work progress thanks to good cutting performance.
- Maximum economic efficiency due to maximum tool life.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.

D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
Flat design EHT (shape 41) 							
105	1	16	14,500	A	25	69121043	EHT 105-1,0 SG STEELOX/16,0
115	1	22.23	13,300	A	25	61340412	EHT 115-1,0 SG STEELOX
	1.6	22.23	13,300	A	25	61340422	EHT 115-1,6 SG STEELOX
	2.4	22.23	13,300	A	25	61340432	EHT 115-2,4 SG STEELOX
125	1	22.23	12,200	A	25	61341112	EHT 125-1,0 SG STEELOX
	1.6	22.23	12,200	A	25	61341122	EHT 125-1,6 SG STEELOX
	2	22.23	12,200	A	25	61320120	EHT 125-2,0 SG STEELOX
	2.4	22.23	12,200	A	25	61331432	EHT 125-2,4 SG STEELOX
150	1.6	22.23	10,200	A	25	61342122	EHT 150-1,6 SG STEELOX
	2	22.23	10,200	A	25	61342400	EHT 150-2,0 SG STEELOX
	2.5	22.23	10,200	A	25	61100150	EHT 150-2,5 SG STEELOX
180	1.6	22.23	8,500	A	25	61326410	EHT 180-1,6 SG STEELOX
	2	22.23	8,500	A	25	69901412	EHT 180-2,0 SG STEELOX
	2.5	22.23	8,500	A	25	61326422	EHT 180-2,5 SG STEELOX
230	1.9	22.23	6,600	A	25	61328430	EHT 230-1,9 SG STEELOX
	2	22.23	6,600	A	25	61328400	EHT 230-2,0 SG STEELOX
	2.5	22.23	6,600	A	25	61328422	EHT 230-2,5 SG STEELOX
	3.2	22.23	6,600	A	25	61328432	EHT 230-3,2 SG STEELOX

Flat design EHT (type 41) with X-LOCK holder X-LOCK

125	1	22.23	12,200	A	25	61341113	EHT 125-1,0 SG STEELOX/X-LOCK
	1.6	22.23	12,200	A	25	61341123	EHT 125-1,6 SG STEELOX/X-LOCK

Depressed-centre design EH (shape 42)

115	2.4	22.23	13,300	A	25	61340123	EH 115-2,4 SG STEELOX
	3.2	22.23	13,300	A	25	61332432	EH 115-3,2 SG STEELOX
125	2.4	22.23	12,200	A	25	61341222	EH 125-2,4 SG STEELOX
	3.2	22.23	12,200	A	25	61333432	EH 125-3,2 SG STEELOX
180	2.5	22.23	8,500	A	25	61323223	EH 180-2,5 SG STEELOX
230	2.5	22.23	6,600	A	25	61324223	EH 230-2,5 SG STEELOX

Depressed-centre design EH (type 42) with X-LOCK holder X-LOCK

125	2.4	22.23	12,200	A	25	61340125	EH 125-2,4 SG STEELOX/X-LOCK
-----	-----	-------	--------	---	----	----------	------------------------------



SG CLASSIC STEELOX ★★☆☆

Cut-off wheel for steel and stainless steel (INOX) with high cutting performance and maximum tool life. Suitable for cutting sheet metal, profiles and solid material, and for cutting out holes.

Special features:

- Fast work progress thanks to good cutting performance.
- Maximum economic efficiency due to maximum tool life.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.

D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
Flat design EHT (shape 41)							
125	1	22.23	12,200	A	25	61341106	EHT 125-1,0 SG CLASSIC STEELOX
	1.6	22.23	12,200	A	25	61341120	EHT 125-1,6 SG CLASSIC STEELOX
180	1.6	22.23	8,600	A	25	61326406	EHT 180-1,6 SG CLASSIC STEELOX



SG INOX ★★☆☆

Cut-off wheel for stainless steel (INOX) with high cutting performance and maximum tool life. Suitable for cutting sheet metal, profiles and solid material, and for cutting out holes.



Special features:

- Fast work progress thanks to good cutting performance.
- Maximum economic efficiency due to maximum tool life.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.


D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
Flat design EHT (shape 41)							
105	1	16	14,500	A	25	61315113	EHT 105-1,0 SG INOX/16,0
115	0.8	22.23	13,300	A	25	61340396	EHT 115-0,8 SG INOX
	1	22.23	13,300	A	25	61340416	EHT 115-1,0 SG INOX
	1.6	22.23	13,300	A	25	61340424	EHT 115-1,6 SG INOX
125	0.8	22.23	12,200	A	25	61341096	EHT 125-0,8 SG INOX
	1	22.23	12,200	A	25	61341116	EHT 125-1,0 SG INOX
	1.6	22.23	12,200	A	25	61341124	EHT 125-1,6 SG INOX
150	1.6	22.23	10,200	A	25	61342124	EHT 150-1,6 SG INOX
180	1.6	22.23	8,500	A	25	61326124	EHT 180-1,6 SG INOX
	2.5	22.23	8,500	A	25	61326423	EHT 180-2,5 SG INOX
230	1.9	22.23	6,600	A	25	61328124	EHT 230-1,9 SG INOX
	2.5	22.23	6,600	A	25	61328423	EHT 230-2,5 SG INOX

Continued on next page



D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-------------	-----------	----------	----------	---	----------	-------------

Depressed-centre design EH (shape 42)



115	2.4	22.23	13,300	A	25	61340124	EH 115-2,4 SG INOX
125	2.4	22.23	12,200	A	25	61341223	EH 125-2,4 SG INOX
180	2.5	22.23	8,500	A	25	61323224	EH 180-2,5 SG INOX
230	2.5	22.23	6,600	A	25	61324224	EH 230-2,5 SG INOX



SG ALU ★★☆☆

Cut-off wheel for aluminium and other non-ferrous metals with high cutting performance and maximum tool life. Suitable for cutting sheet metal, profiles and solid material, and for cutting out holes.



Special features:

- Special abrasive mixture and bond technology prevent the cut-off wheel clogging up, even on soft, tough aluminium.
- Does not contain any fillers that could leave undesirable residues on the work-piece. The surface can therefore be welded immediately.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.


D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-------------	-----------	----------	----------	---	----------	-------------

Flat design EHT (shape 41)



105	1	16	14,500	A/C	25	61339430	EHT 105-1,0 SG ALU/16,0
115	1	22.23	13,300	A/C	25	61340415	EHT 115-1,0 SG ALU
	1.6	22.23	13,300	A/C	25	61340425	EHT 115-1,6 SG ALU
	2.4	22.23	13,300	A/C	25	61340550	EHT 115-2,4 SG ALU
125	1	22.23	12,200	A/C	25	61341115	EHT 125-1,0 SG ALU
	1.6	22.23	12,200	A/C	25	61341225	EHT 125-1,6 SG ALU
	2.4	22.23	12,200	A/C	25	61331550	EHT 125-2,4 SG ALU
150	1.6	22.23	10,200	A/C	25	61323116	EHT 150-1,6 SG ALU
180	1.6	22.23	8,500	A/C	25	61326119	EHT 180-1,6 SG ALU
	2.9	22.23	8,500	A/C	25	61326323	EHT 180-2,9 SG ALU
230	1.9	22.23	6,600	A/C	25	61328119	EHT 230-1,9 SG ALU
	2.9	22.23	6,600	A/C	25	61328323	EHT 230-2,9 SG ALU

Depressed-centre design EH (shape 42)



115	2.4	22.23	13,300	A/C	25	61340312	EH 115-2,4 SG ALU
125	2.4	22.23	12,200	A/C	25	61320822	EH 125-2,4 SG ALU
180	2.9	22.23	8,500	A/C	25	61323323	EH 180-2,9 SG ALU
230	2.9	22.23	6,600	A/C	25	61324323	EH 230-2,9 SG ALU




CERAMIC SGP STEEL ★★★★★

Special cut-off wheel with ceramic oxide grain for steel with ultimate cutting performance and excellent tool life. Suitable for cutting large cross-sections, profiles and solid material, and for cutting out holes.



Special features:

- Extremely fast work progress, even with large cross-sections.
- Previously unattained cutting performance thanks to high-performance abrasive ceramic oxide grain in conjunction with a special bond technology.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.

D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
Flat design EHT (shape 41) 							
100	1.3	16	15,300	CO	25	61301013	EHT 100-1,3 CERAMIC SGP STEEL/16,0
115	1	22.23	13,300	CO	25	61301510	EHT 115-1,0 CERAMIC SGP STEEL
	1.6	22.23	13,300	CO	25	61301516	EHT 115-1,6 CERAMIC SGP STEEL
125	1	22.23	12,200	CO	25	61312510	EHT 125-1,0 CERAMIC SGP STEEL
	1.6	22.23	12,200	CO	25	61312516	EHT 125-1,6 CERAMIC SGP STEEL
	2	22.23	12,200	CO	25	61312520	EHT 125-2,0 CERAMIC SGP STEEL
150	1.6	22.23	10,200	CO	25	61315016	EHT 150-1,6 CERAMIC SGP STEEL
180	1.6	22.23	8,500	CO	25	61318016	EHT 180-1,6 CERAMIC SGP STEEL
	2.5	22.23	8,500	CO	25	61318025	EHT 180-2,5 CERAMIC SGP STEEL
230	1.9	22.23	6,600	CO	25	61323019	EHT 230-1,9 CERAMIC SGP STEEL
	2.5	22.23	6,600	CO	25	61323025	EHT 230-2,5 CERAMIC SGP STEEL
Depressed-centre design EH (shape 42) 							
115	1.6	22.23	13,300	CO	25	61300115	EH 115-1,6 CERAMIC SGP STEEL
125	1.6	22.23	12,200	CO	25	61300125	EH 125-1,6 CERAMIC SGP STEEL



Cut-off wheels

Special Line SGP ★★★★★



SGP STEELOX ★★★★★

Cut-off wheel for steel and stainless steel (INOX) with high cutting performance and an excellent tool life. Suitable for cutting thin sheet and profiles, and for cutting out holes.



Special features:

- Excellent tool life on thin sheet metal and profiles thanks to wear-resistant bond system.
- Fast work progress thanks to good cutting performance.
- Thin cut-off wheels are ergonomically optimised, efficient and provide impressively fast and thin cuts with minimized burr formation.

D [mm]	T [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-----------	-----------	----------	----------	--	----------	-------------

Flat design EHT (shape 41)

105	0.8	16	14,500	A	25	61330008	EHT 105-0,8 SGP STEELOX/16,0
	1	16	14,500	A	25	61330012	EHT 105-1,0 SGP STEELOX/16,0
115	0.8	22.23	13,300	A	25	61340394	EHT 115-0,8 SGP STEELOX
	1	22.23	13,300	A	25	61330421	EHT 115-1,0 SGP STEELOX
	1.6	22.23	13,300	A	25	61330420	EHT 115-1,6 SGP STEELOX
	2.2	22.23	13,300	A	25	61330422	EHT 115-2,2 SGP STEELOX
125	0.8	22.23	12,200	A	25	61341094	EHT 125-0,8 SGP STEELOX
	1	22.23	12,200	A	25	61331421	EHT 125-1,0 SGP STEELOX
	1.6	22.23	12,200	A	25	61331420	EHT 125-1,6 SGP STEELOX
	2.2	22.23	12,200	A	25	61331622	EHT 125-2,2 SGP STEELOX
150	1.6	22.23	10,200	A	25	61342164	EHT 150-1,6 SGP STEELOX
	2.5	22.23	10,200	A	25	61342225	EHT 150-2,5 SGP STEELOX
180	1.6	22.23	8,500	A	25	61343122	EHT 180-1,6 SGP STEELOX
230	1.9	22.23	6,600	A	25	61328702	EHT 230-1,9 SGP STEELOX
	2.3	22.23	6,600	A	25	61328712	EHT 230-2,3 SGP STEELOX
	2.8	22.23	6,600	A	25	61328722	EHT 230-2,8 SGP STEELOX

Clamping flanges



Clamping flange set for thin 180/230 mm cut-off wheels

Clamping flange set for increasing lateral stability and precise guidance in order to prevent wobbling, especially when using cut-off wheels from 1.6 to 2.0 mm in width with diameters of 180 and 230 mm. The set can be used with any standard angle grinder with an M14 or 5/8"-11 drive spindle.

For angle grinders with a spindle	D [mm]		Item no.	Designation
M 14	76	1	33500760	SFS 76 M14
5/8"-11	76	1	33500761	SFS 76 5/8"-11

Cut-off wheels for foundries

Performance Line SG ★★☆☆



SG CAST + INOX ★★☆☆

Cut-off wheel optimized for use in harsh conditions in foundries and fettling shops with high cutting performance, good tool life and high lateral stability. Suitable for cutting cast iron, stainless steel (INOX) and cast steel.

Special features:

- The reinforced fabric armoring for tough foundry applications guarantees the highest degree of safety.
- Fast work progress due to high cutting performance and high efficiency thanks to excellent tool life.
- Optimized for use on compressed-air turbine and high-frequency angle grinders.


D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-------------	-----------	----------	----------	--	----------	-------------

Flat design EHT (shape 41)



230	2.9	22.23	6,600	A	25	61328832	EHT 230-2,9 SG CAST+INOX
-----	-----	-------	-------	---	----	----------	--------------------------

Depressed-centre design EH (shape 42)



230	2.9	22.23	6,600	A	25	61324832	EH 230-2,9 SG CAST+INOX
-----	-----	-------	-------	---	----	----------	-------------------------



SG CAST + ALU ★★☆☆

Cut-off wheel optimized for use in harsh conditions in foundries and fettling shops with high cutting performance, good tool life and high lateral stability. Suitable for cutting grey/nodular cast iron (GG/GJL, GGG/GJS) and hard aluminium alloys.

Special features:

- The reinforced fabric armoring for tough foundry applications guarantees the highest degree of safety.
- Fast work progress due to high cutting performance and high efficiency thanks to excellent tool life.
- Optimized for use on compressed-air turbine and high-frequency angle grinders.

D [mm]	T/U [mm]	H [mm]	Max. RPM	Abrasive		Item no.	Designation
-----------	-------------	-----------	----------	----------	--	----------	-------------

Depressed-centre design EH (shape 42)



230	3.2	22.23	6,600	A/C	25	61324802	EH 230-3,2 SG CAST+ALU
-----	-----	-------	-------	-----	----	----------	------------------------

6

