ADVANCE ANTI-SLIP SURFACES P/L — 30 years

The ideal solution for preventing costly accidents in slippery areas



STAIR NOSINGS

Advance Anti-Slip Stair Nosings are a Class One, ready to install, metal backed product with a durable antislip surface designed for application in slippery or hazardous areas to provide firm footing.

Stair Nosings can be produced to suit any type of stair, ie: Steel mesh/grating or grille, checkerplate, concrete, timber, FRP, etc...




STANDARD SIZE COMBINATIONS

Width (A)	+ Depth (B)	+ Return (C)
350 mm	50 mm	10 mm
450 mm	75 mm	20 mm
600 mm	150 mm	25 mm
750 mm	215 mm	
900 mm		
1200 mm		

Custom sizes available, Made To Order

HOW TO MEASURE



METHOD OF INSTALLATION

Over Grille: Use universal clamp assembly.

Over Steel-Aluminium-Masonry-Timber: Use self-tapping screws, countersunk screws or rivets with a silicon sealer under the edges.

Over Concrete: Drive nails with a silicon sealer under the edges.

PRODUCT FEATURES

- Provides secure footing on wet & oily surfaces.
- Highlights leading edge of step.
- High impact resistance.
- Excellent chemical & UV resistance.
- Pre-Drilled for simple installation.
- Durable with a long effective life.

GRADES

BF	= Barefoot	80
Fine	= Fine	46
Ind	= Industrial	24
HD	= Heavy Duty	20
OS	= Offshore	16

FOUNDATIONS

GL	=	Galvabond® 1.2mm
GL3	=	Galvabond® 3.0mm
AL1.6	=	5052 Aluminium 1.6mm
AL3	=	5052 Aluminium 3.0mm
SS1.2	=	316 Stainless Steel 1.2mm
SS1.6	=	316 Stainless Steel 1.6mm

LADDER RUNG COVERS

Advance Anti-Slip Ladder Rung Covers with the Semi Circular or Rectangular bend are a Class One, ready to install, metal backed product with a durable antislip surface designed to provide firm footing on any type of ladder.

Circular ladder rung covers snap fit to any type of round ladder rung. Easy to install with a sealant adhesive.




STANDARD SIZE COMBINATIONS

Width (A)	+ Diameter of Rung (B)
250 mm	20 mm
300 mm	25 mm
350 mm	30 mm
400 mm	35 mm
450 mm	
500 mm	

Custom sizes available, Made To Order

HOW TO MEASURE



METHOD OF INSTALLATION

Ensure the ladder rungs are free from all dirt, oil, grease and paint.

Apply 5mm of sealant adhesive to the inside of the ladder rung.

Snap fit to ladder rung.

PRODUCT FEATURES

- Provides secure footing on wet & oily surfaces.
- High impact resistance.
- Excellent chemical & UV resistance.
- Long effective life.
- Easy to clean.

GRADES

Fine	= Fine	46
Ind	= Industrial	24
HD	= Heavy Duty	20
OS	= Offshore	16

FOUNDATIONS

Circular

CB	=	Colorbond® .55mm
AL.8	=	5052 Aluminium .8mm
SS.55	=	316 Stainless Steel .55mm

Square

GL	=	Galvabond® 1.2mm
AL1.6	=	5052 Aluminium 1.6mm
SS1.2	=	316 Stainless Steel 1.2mm

www.advanceantislip.com

sales@advanceantislip.com