# BERNARD STYLE 400 TORCH

| BND400 TORCH | |
|---|---|
| Current | 400 Amps |
| Duty Cycle @ 40°C | 60% @ 400Amp CO2<br>60% @ 320Amp MIX |
| Cooling | Air |
| Wire Size | 0.8mm > 2.0mm |




| | Part No. | Description |
|---|---|---|
| | 93.4412.AE | Bernard Style 400A Complete MIG Torch Euro Connect 3.5Mt |
| | 93.4415.AE | Bernard Style 400A Complete MIG Torch Euro Connect 4.5Mt |
| 1 | 93.4491 | ø 19mm - 3/4" Cylindrical Insulated Gas Nozzle OT (400/500) |
| 2 | 93.4492 | ø 14mm - 9/16" Conical Insulated Gas Nozzle OT (400/500) |
| 3 | 93.4591 | ø 19mm - 3/4" Cylindrical Insulated Gas Nozzle CU (400/500) |
| 4 | 93.4592 | ø 14mm - 9/16" Conical Insulated Gas Nozzle CU (400/500) |
| 5 | 93.7497 | Contact Tip 0.6mm Standard |
| | 93.7488 | Contact Tip 0.8mm Standard |
| | 93.7489 | Contact Tip 0.9mm Standard |
| | 93.7496 | Contact Tip 1.0mm Standard |
| | 93.7490 | Contact Tip 1.2mm Standard |
| | 93.7498 | Contact Tip 1.4mm Standard |
| | 93.7491 | Contact Tip 1.6mm Standard |
| | 93.7492 | Contact Tip 2.0mm Standard |
| 6 | 93.1589 | Contact Tip 0.9mm Long |
| | 93.1596 | Contact Tip 1.0mm Long |
| | 93.1590 | Contact Tip 1.2mm Long |
| | 93.1598 | Contact Tip 1.4mm Long |
| | 93.1592 | Contact Tip 2.0mm Long |
| 7 | 93.4435 | Gas Diffuser (400/500) |
| 8 | 93.7127 | O Ring (400/500) |
| 9 | 93.4423 | Insulator (400/500) |
| 10 | 93.4790 | Swan Neck (400) |
| 11 | 93.4794 | Swan Neck (500) |
| 12 | 93.4422 | Trigger Switch (400/500) |
| 13 | 93.44115 | Steel Liner 0.9—1.2mm 4.6Mt |
| | 93.44215 | Steel Liner 1.2—1.6mm 4.6Mt |
| 14 | 93.44215X | Teflon Liner Aluminium 1.2—1.6mm 4.6Mt |











































