



TECHNICAL DATA SHEET

CRC 5-56 Marine



CRC 5-56 Marine is a multi-purpose lubricant designed to prevent damage due to water and salt atmosphere in marine engines and boating equipment.

It forms a thin film that lubricates moving parts for smooth action and protects metals from corrosion caused by humidity and salt air for extended periods.

CRC 5-56 Marine repels water, prevents ingress and starts wet engines. It frees corroded parts on vehicles, trailers, springs, shackles, domes and zips.

CRC 5-56 Marine lubricates all mechanical parts and penetrates overtight or rusted nuts, bolts and fittings.

Item Code: 6006

Pack Size: 300g Aerosol

Features and Benefits

- **Lubrication for smooth action:** Silences annoying squeaks and squeals
- **Stops and attacks rust:** Protective film for ongoing protection against corrosion
- **Displaces moisture to help start wet engines**
- **Penetrates quickly:** Breaks away rust and corrosion, frees components bonded by dirt and scale
- **Preventative maintenance programs:** To increase the life expectancy of mechanical equipment
- **Safe for all metals and alloys,** most painted surfaces, coatings, plastics and rubbers
- **Contains no silicone**
- **Cleans grease and tar off painted surfaces**

Applications

CRC 5-56 Marine has multiple applications in marine environments.

- Engines and outboards
- Boating equipment
- Trailer maintenance
- General marine use

Typical Properties and Characteristics

Flash Point	73°C
Odour	Pleasant odour
Appearance	Amber Liquid
Solubility	Insoluble in water
Type of film	Thin penetrating oil, non-drying

Flammability	Flammable
Boiling Point	193°C
% Volatile	82%
Vapour Density	> Air
Specific Gravity	0.81
Propellant	Hydrocarbon



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au



TECHNICAL DATA SHEET

CRC 5-56 Marine

Directions

1. Do NOT spray while equipment is energised.
2. Hold can 30cm away from surface and spray liberally.
3. For greater penetration, leave to soak in, before working on part.
4. Wipe away excess fluid with a clean cloth.
5. For starting flooded engines, spray all electrics and leads liberally.

Note: When cleaning surfaces, test a small area first for colour fastness.

Special Precautions

General:

Flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Dispose of contents/container in accordance with relevant regulations.

Pressurized container: may burst if heated. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 05/2026



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au